



**RIF. COD.**

1	B000028A04	43	C710701N01
2	C416100A01	44	B000028A22
3	C416103A02	45	B000028B01
4	D416123C01	46	C710990N01
5	B000020A59	47	D710954N01
6	B000020A25	48	B000028B01
7	C216160A01	49	C016562B01
8	B000020A19	50	B000022A01
9	C016200A01	51	B000028B06
10	D416202C01	52	B000028B02
11	B000020A32	53	C710542N01
12	B000020A31	54	B000028A02
13	B000020A29	55	B000028A01
14	C016220A01	56	C710500N01
15	B000025A06	57	B000021C01
16	C416225M03	58	C416421A01
17	B000020A35	59	C216424A01
18	D416241C01	60	D710939N01
19	B000020A22	61	C710822N01
20	C016244A01	62	C710820N01
21	B000020A17	63	D710729N01
22	D416302A01	64	B000028A20
23	B000020A01	65	B000028E15
24	B000020A03	66	C230842A02
25	D416361A01	67	C710860N01
26	C216340A01	68	C710884N01
27	B000020A14	69	D416123C01
28	D416345A01	70	D416202C01
29	B000020A14	71	D416226M03
30	B000020A18	72	D416241C01
31	D416322A01	73	D416302A01
32	B000027B03	74	D416361A01
33	C710400N01	75	D216283A01
34	C425262A01		
35	B000020A36		
36	D216283A01		
37	C710261N01		
38	B000021C03		
39	C710402N01		
40	C650698A03		
41	B000028E05		
42	B000023B01		

Codice **A710000M09**  
Modello **M10**  
Tipo Punto **MG**  
Lungh. min. **12 mm.**  
Lungh. max. **30 mm.**

Kode **A710000M09**  
Modell **M10**  
Klammer Typ **MG**  
Min. Länge **12 mm.**  
Max. Länge **30 mm.**

Code **A710000M09**  
Model **M10**  
Staple type **MG**  
Min. length **12 mm.**  
Max. length **30 mm.**

Code **A710000M09**  
Modèle **M10**  
Agrafe type **MG**  
Longueur min. **12 mm.**  
Longueur max. **30 mm.**

Código **A710000M09**  
Modelo **M10**  
Grapa tipo **MG**  
Largueza min. **12 mm.**  
Largueza max. **30 mm.**

Codigo **A710000M09**  
Modelo **M10**  
Tipo de agrafe **MG**  
Largura min. **12 mm.**  
Largura max. **30 mm.**

**DATI TECNICI**

Peso: **990 gr.**  
Dimensioni: **44-180-235 mm.**  
Consumo aria: **0,28 NI/colpo (6 bar)**  
Pressione min.: **4,0 bar**  
Pressione max.: **7,0 bar**

**TECHNISCHE DATEN**

Gewicht: **990 gr.**  
Abmessungen: **44-180-235 mm.**  
Luftverbrauch: **0,28 NI/pro Schlag (6 bar)**  
Min.Betriebsdruck: **4,0 bar**  
Max.Betriebsdruck: **7,0 bar**

**TECHNICAL FEATURES**

Weight: **990 gr.**  
Dimensions: **44-180-235 mm.**  
Air consumption: **0,28 NI/shot (6 bar)**  
Min.working pressure: **4,0 bar**  
Max.working pressure: **7,0 bar**

**DONNEES TECHNIQUES**

Poids: **990 gr.**  
Dimensions: **44-180-235 mm.**  
Consommation d'air: **0,28 NI/coup (6 bar)**  
Pression de fonction min.: **4,0 bar**  
Pression de fonction max.: **7,0 bar**

**DATOS TECNICOS**

Peso: **990 gr.**  
Dimensiones: **44-180-235 mm.**  
Consumo de aire: **0,28 NI/disparo (6 bar)**  
Presion min.: **4,0 bar**  
Presion max.: **7,0 bar**

**CARACTERISTICAS TECNICAS**

Peso: **990 gr.**  
Dimensões: **44-180-235 mm.**  
Consumo de ar: **0,28 NI/disparo (6 bar)**  
Pressão min.: **4,0 bar**  
Pressão max.: **7,0 bar**

**POTENZA ACUSTICA**

DIRETTIVA CEE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **81,7 (dB)**  
LpA 60S 1M= **80,2 (dB)**

**SCHALLEISTUNG**

EWG RICHTLINIE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **81,7 (dB)**  
LpA 60S 1M= **80,2 (dB)**

**NOISE POWER**

EEC DIRECTIVE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **81,7 (dB)**  
LpA 60S 1M= **80,2 (dB)**

**PUISSANCE ACOUSTIQUE**

DIRECTIVE CEE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **81,7 (dB)**  
LpA 60S 1M= **80,2 (dB)**

**POTENCIA ACUSTICA**

NORMATIVA CEE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **81,7 (dB)**  
LpA 60S 1M= **80,2 (dB)**

**POTENCIA ACUSTICA**

DIRETTIVA CEE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **81,7 (dB)**  
LpA 60S 1M= **80,2 (dB)**

**B610040D01 O-Ring Kit**

**VIBRAZIONI PRODOTTE**

DIRETTIVA CEE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **inferiore a 2,5 (m/s<sup>2</sup>)**

**GERAETEBOZGENER**

**VIBRATIONSWEIT**  
EWG RICHTLINIE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **inferiore a 2,5 (m/s<sup>2</sup>)**

**TOOL RELATED VIBRATION**

**VALUE**  
EEC DIRECTIVE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **inferiore a 2,5 (m/s<sup>2</sup>)**

**VALEUR DES VIBRATIONS**

**PAR LA MACHINE**  
DIRECTIVE CEE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **inferiore a 2,5 (m/s<sup>2</sup>)**

**VIBRACION PRODUCIDA**

NORMATIVA CEE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **inferiore a 2,5 (m/s<sup>2</sup>)**

**NIVEL DE VIBRAÇÃO**

**DO PRODUTO**  
DIRETTIVA CEE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **inferiore a 2,5 (m/s<sup>2</sup>)**

**710/0 M09/03 05/03**