



<u>RIF.</u>	<u>COD.</u>			<u>DATI TECNICI</u>	<u>POTENZA ACUSTICA</u>	<u>VIBRAZIONI PRODOTTE</u>
1	B000028A04	43	B000028B01	Codice A710000N03	Peso: 1150 gr.	DIRETTIVA CEE
2	C416100A01	44	C710990N01	Modello M10	Dimensioni: 44-202-235 mm.	ISO-11148-13-2017
3	C416103A02	45	D710954N03	Tipo Punto MG	Consumo aria: 0,30 NI/colpo (6 bar)	prEN 12549 (1999)
4	D710123N01	46	B000028B01	Lungh. min. 12 mm.	Pressione min.: 4,0 bar	UNI EN ISO 3744 (1997)
5	B000020A59	47	C016562B01	Lungh. max. 40 mm.	Pressione max.: 7,0 bar	LwA= 81,7 (dB)
6	B000020A25	48	B000028B06			LpA 60S 1M= 80,2 (dB)
7	C216160A01	49	B000028B03	Kode A710000N03	<u>TECHNISCHE DATEN</u>	<u>SCHALLELEISTUNG</u>
8	B000020A19	50	C710681N03	Modell M10	Gewicht: 1150 gr.	EWG RICHTLINIE
9	C016200A01	51	C216661B01	Klammer Typ MG	Abmessungen: 44-202-235 mm.	ISO-11148-13-2017
10	D416202C01	52	C710600N03	Min. Länge 12 mm.	Luftverbrauch: 0,30 NI/pro Schlag (6 bar)	prEN 12549 (1999)
11	B000020A32	53	B000021C01	Max. Länge 40 mm.	Min.Betriebsdruck: 4,0 bar	UNI EN ISO 3744 (1997)
12	B000020A31	54	C710542N03		Max.Betriebsdruck: 7,0 bar	LwA= 81,7 (dB)
13	B000020A29	55	B000028A02	Code A710000N03	<u>TECHNICAL FEATURES</u>	LpA 60S 1M= 80,2 (dB)
14	C016220A01	56	B000028A01	Model M10	Weight: 1150 gr.	<u>NOISE POWER</u>
15	B000025A06	57	C710500N03	Staple type MG	Dimensions: 44-202-235 mm.	EEC DIRECTIVE
16	C710225N01	58	B000021C01	Min. length 12 mm.	Air consumption: 0,30 NI/shot (6 bar)	ISO-11148-13-2017
17	B000020A35	59	C016483B01	Max. length 40 mm.	Min.working pressure: 4,0 bar	prEN 12549 (1999)
18	D416241U02	60	C216424A01		Max.working pressure: 7,0 bar	UNI EN ISO 3744 (1997)
19	B000020A22	61	D710939N03	Code A710000N03	<u>DONNEES TECHNIQUES</u>	LwA= 81,7 (dB)
20	C016244A01	62	C710822N03	Modèle M10	Poids: 1150 gr.	LpA 60S 1M= 80,2 (dB)
21	B000020A17	63	C710820N01	Agrafe type MG	Dimensions: 44-202-235 mm.	<u>PUISSANCE ACOUSTIQUE</u>
22	D416302A01	64	D710729N03	Longueur min. 12 mm.	Consommation d'air: 0,30 NI/coup (6 bar)	DIRECTIVE CEE
23	B000020A01	65	B000028A20	Longueur max. 40 mm.	Pression de fonction min.: 4,0 bar	ISO-11148-13-2017
24	B000020A03	66	B000028E15		Pression de fonction max.: 7,0 bar	prEN 12549 (1999)
25	D416361A01	67	C230842A02	Código A710000N03	<u>DATOS TECNICOS</u>	UNI EN ISO 3744 (1997)
26	C216340A01	68	C710860N03	Modelo M10	Peso: 1150 gr.	LwA= 81,7 (dB)
27	B000020A14	69	C710884N01	Grapa tipo MG	Dimensiones: 44-202-235 mm.	LpA 60S 1M= 80,2 (dB)
28	D416345A01	70	D710123N01	Largueza min. 12 mm.	Consumo de aire: 0,30 NI/disparo (6 bar)	<u>POTENCIA ACUSTICA</u>
29	B000020A14	71	D416202C01	Largueza max. 40 mm.	Presion min.: 4,0 bar	NORMATIVA CEE
30	B000020A18	72	D710226N01		Presion max.: 7,0 bar	ISO-11148-13-2017
31	D416322A01	73	D416241U02	Codigo A710000N03	<u>CARACTERISTICAS TECNICAS</u>	prEN 12549 (1999)
32	B000027B03	74	D416302A01	Modelo M10	Peso: 1150 gr.	UNI EN ISO 3744 (1997)
33	C416431B01	75	D416361A01	Tipo de agrafe MG	Dimensões: 44-202-235 mm.	LwA= 81,7 (dB)
34	C425262A01	76	D216283A01	Largura min. 12 mm.	Consumo de ar: 0,30 NI/disparo (6 bar)	LpA 60S 1M= 80,2 (dB)
35	B000020A36			Largura max. 40 mm.	Pressão min.: 4,0 bar	<u>POTENCIA ACUSTICA</u>
36	D216283A01				Pressão max.: 7,0 bar	DIRETTIVA CEE
37	C710261N01					ISO-11148-13-2017
38	C430401A02					prEN 12549 (1999)
39	B000028E05					UNI EN ISO 3744 (1997)
40	B000023B01					LwA= 81,7 (dB)
41	C710701N01					LpA 60S 1M= 80,2 (dB)
42	B000028A22					
						<u>TOOL RELATED VIBRATION VALUE</u>
						EEC DIRECTIVE
						ISO-11148-13-2017
						ISO/FDIS 8662-11 (1999)
						ah.w.3s= inferiore a 2,5 (m/s²)
						<u>VALOR DES VIBRATIONS PAR LA MACHINE</u>
						DIRECTIVE CEE
						ISO-11148-13-2017
						ISO/FDIS 8662-11 (1999)
						ah.w.3s= inferiore a 2,5 (m/s²)
						<u>VIBRACION PRODUCIDA</u>
						NORMATIVA CEE
						ISO-11148-13-2017
						ISO/FDIS 8662-11 (1999)
						ah.w.3s= inferiore a 2,5 (m/s²)
						<u>NIVEL DE VIBRAÇÃO DO PRODUTO</u>
						DIRETTIVA CEE
						ISO-11148-13-2017
						ISO/FDIS 8662-11 (1999)
						ah.w.3s= inferiore a 2,5 (m/s²)
						B610040D01 O-Ring Kit
						710/0 N03/02 14/06