



RIF. COD.

1	B000028A10	43	B000020A01
2	C425100A01	44	B000020A03
3	D425123A01	45	D715361A01
4	B000020A40	46	C216340A01
5	B000020A39	47	B000020A14
6	C225160A01	48	D425345A01
7	B000020A04	49	B000020A14
8	C016200A01	50	B000020A18
9	D425202A01	51	D416322A01
10	B000020A36	52	C016400A01
11	B000020A33	53	D615440A01
12	C425220A01	54	B000026A15
13	B000025A12	55	B000020A36
14	C425225A08	56	D425283A01
15	B000020A31	57	B000023B02
16	C425242A01	58	D425123A01
17	B000020A39	59	D425202A01
18	D425241A01	60	D425226A08
19	B000020A24	61	D425241A01
20	C225244A01	62	D416302A01
21	C615261A01	63	D715361A01
22	B000028B06	64	D615440A01
23	C425540A02	65	D425283A01
24	C425500A01	66	D225984A02
25	C425722A03	67	B000028A03
26	C620424A01	68	C416990A02
27	B000021C01		
28	B000028A09		
29	C425987A01		
30	C016761A01		
31	C425760A02		
32	C416763A01		
33	B000021C01		
34	B000026A05		
35	C225824A01		
36	C225820A01		
37	C216842A01		
38	C225860A01		
39	D225984A02		
40	C225884A01		
41	B000020A17		
42	D416302A01		

Codice **A715000A03**
Modello **M15**
Tipo Punto **92**
Lungh. min. **10 mm.**
Lungh. max. **25 mm.**

Kode **A715000A03**
Modell **M15**
Klammer Typ **92**
Min. Länge **10 mm.**
Max. Länge **25 mm.**

Code **A715000A03**
Model **M15**
Staple type **92**
Min. length **10 mm.**
Max. length **25 mm.**

Code **A715000A03**
Modèle **M15**
Agrafe type **92**
Longueur min. **10 mm.**
Longueur max. **25 mm.**

Código **A715000A03**
Modelo **M15**
Grapa tipo **92**
Largueza min. **10 mm.**
Largueza max. **25 mm.**

Codigo **A715000A03**
Modelo **M15**
Tipo de agrafe **92**
Largura min. **10 mm.**
Largura max. **25 mm.**

DATI TECNICI

Peso: **1070 gr.**
Dimensioni: **55-182-222 mm.**
Consumo aria: **0,49 NI/colpo (6 bar)**
Pressione min.: **4,0 bar**
Pressione max.: **7,0 bar**

TECHNISCHE DATEN

Gewicht: **1070 gr.**
Abmessungen: **55-182-222 mm.**
Luftverbrauch: **0,49 NI/pro Schlag (6 bar)**
Min.Betriebsdruck: **4,0 bar**
Max.Betriebsdruck: **7,0 bar**

TECHNICAL FEATURES

Weight: **1070 gr.**
Dimensions: **55-182-222 mm.**
Air consumption: **0,49 NI/shot (6 bar)**
Min.working pressure: **4,0 bar**
Max.working pressure: **7,0 bar**

DONNEES TECHNIQUES

Poids: **1070 gr.**
Dimensions: **55-182-222 mm.**
Consommation d'air: **0,49 NI/coup (6 bar)**
Pression de fonction min.: **4,0 bar**
Pression de fonction max.: **7,0 bar**

DATOS TECNICOS

Peso: **1070 gr.**
Dimensiones: **55-182-222 mm.**
Consumo de aire: **0,49 NI/disparo (6 bar)**
Presion min.: **4,0 bar**
Presion max.: **7,0 bar**

CARACTERISTICAS TECNICAS

Peso: **1070 gr.**
Dimensões: **55-182-222 mm.**
Consumo de ar: **0,49 NI/disparo (6 bar)**
Pressão min.: **4,0 bar**
Pressão max.: **7,0 bar**

POTENZA ACUSTICA

DIRETTIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

SCHALLEISTUNG

EWG RICHTLINIE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

NOISE POWER

EEC DIRECTIVE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

POTENCIA ACUSTICA

NORMATIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

POTENCIA ACUSTICA

DIRETTIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

B615040A01 O-Ring Kit

VIBRAZIONI PRODOTTE

DIRETTIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inferiore a 2,5 (m/s²)**

GERAETEBEZOGENER

VIBRATIONSWERT
EWG RICHTLINIE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **unter 2,5 (m/s²)**

TOOL RELATED VIBRATION

VALUE
EEC DIRECTIVE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **below 2,5 (m/s²)**

VALEUR DES VIBRATIONS

PAR LA MACHINE
DIRECTIVE CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inférieur á 2,5 (m/s²)**

VIBRACION PRODUCIDA

NORMATIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inferior a 2,5 (m/s²)**

NIVEL DE VIBRACAO

DO PRODUTO
DIRECTIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inferior a 2,5 (m/s²)**

715/0 A03/01 07/11