



RIF. COD.

1	B000028A10	43	B000020A14
2	C425100A01	44	B000020A18
3	D425123A01	45	D416322A01
4	B000020A40	46	C016400A01
5	B000020A39	47	D615440A01
6	C225160A01	48	B000026A15
7	B000020A04	49	B000020A36
8	C016200A01	50	D425283A01
9	D425202A01	51	B000023B02
10	B000020A36	52	C216860D01
11	B000020A33	53	C216841D01
12	C425220A01	54	D225984A04
13	B000025A12	55	C216842A02
14	C425225A10	56	C216840A01
15	B000020A31	57	B000027A05
16	C425242A01	58	D425123A01
17	B000020A39	59	D425202A01
18	D425241A01	60	D425226A10
19	B000020A24	61	D425241A01
20	C225244A01	62	D416302A01
21	C615261A01	63	D715361A01
22	B000028B06	64	D615440A01
23	C425540A04	65	D425283A01
24	C425500A01	66	D225984A04
25	C425722A05	67	B000028A03
26	C620424A01	68	C416990A02
27	B000021C01		
28	B000028A09		
29	C425987A01		
30	C016761A01		
31	C425760A02		
32	C416763A01		
33	B000021C01		
34	B000026A05		
35	B000020A17		
36	D416302A01		
37	B000020A01		
38	B000020A03		
39	D715361A01		
40	C216340A01		
41	B000020A14		
42	D425345A01		

Codice **A715000A05**
Modello **M15**
Tipo Punto **90**
Lungh. min. **10 mm.**
Lungh. max. **25 mm.**

Kode **A715000A05**
Modell **M15**
Klammer Typ **90**
Min. Länge **10 mm.**
Max. Länge **25 mm.**

Code **A715000A05**
Model **M15**
Staple type **90**
Min. length **10 mm.**
Max. length **25 mm.**

Code **A715000A05**
Modèle **M15**
Agrafe type **90**
Longueur min. **10 mm.**
Longueur max. **25 mm.**

Código **A715000A05**
Modelo **M15**
Grapa tipo **90**
Largueza min. **10 mm.**
Largueza max. **25 mm.**

Codigo **A715000A05**
Modelo **M15**
Tipo de agrafe **90**
Largura min. **10 mm.**
Largura max. **25 mm.**

DATI TECNICI

Peso: **1120 gr.**
Dimensioni: **55-182-222 mm.**
Consumo aria: **0,49 NI/colpo (6 bar)**
Pressione min.: **4,0 bar**
Pressione max.: **7,0 bar**

TECHNISCHE DATEN

Gewicht: **1120 gr.**
Abmessungen: **55-182-222 mm.**
Luftverbrauch: **0,49 NI/pro Schlag (6 bar)**
Min.Betriebsdruck: **4,0 bar**
Max.Betriebsdruck: **7,0 bar**

TECHNICAL FEATURES

Weight: **1120 gr.**
Dimensions: **55-182-222 mm.**
Air consumption: **0,49 NI/shot (6 bar)**
Min.working pressure: **4,0 bar**
Max.working pressure: **7,0 bar**

DONNEES TECHNIQUES

Poids: **1120 gr.**
Dimensions: **55-182-222 mm.**
Consommation d'air: **0,49 NI/coup (6 bar)**
Pression de fonction min.: **4,0 bar**
Pression de fonction max.: **7,0 bar**

DATOS TECNICOS

Peso: **1120 gr.**
Dimensiones: **55-182-222 mm.**
Consumo de aire: **0,49 NI/disparo (6 bar)**
Presion min.: **4,0 bar**
Presion max.: **7,0 bar**

CARACTERISTICAS TECNICAS

Peso: **1120 gr.**
Dimensões: **55-182-222 mm.**
Consumo de ar: **0,49 NI/disparo (6 bar)**
Pressão min.: **4,0 bar**
Pressão max.: **7,0 bar**

POTENZA ACUSTICA

DIRETTIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

SCHALLEISTUNG

EWG RICHTLINIE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

NOISE POWER

EEC DIRECTIVE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

POTENCIA ACUSTICA

NORMATIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

POTENCIA ACUSTICA

DIRETTIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

B615040A01 O-Ring Kit

VIBRAZIONI PRODOTTE

DIRETTIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inferiore a 2,5 (m/s²)**

GERAETEBEZOGENER

VIBRATIONSWERT
EWG RICHTLINIE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **unter 2,5 (m/s²)**

TOOL RELATED VIBRATION

VALUE
EEC DIRECTIVE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **below 2,5 (m/s²)**

VALEUR DES VIBRATIONS

PAR LA MACHINE
DIRECTIVE CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inférieur á 2,5 (m/s²)**

VIBRACION PRODUCIDA

NORMATIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inferior a 2,5 (m/s²)**

NIVEL DE VIBRACAO

DO PRODUTO
DIRETTIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inferior a 2,5 (m/s²)**

715/0 A05/01 07/11