



RIF. COD.

1	B000028A10	43	B000022A02
2	C425100A01	44	B000028E14
3	C425103A02	45	B000028B07
4	D425123A01	46	B000028B06
5	B000020A40	47	B000028B03
6	B000020A39	48	C030681B01
7	C225160A01	49	C216661B02
8	B000020A04	50	C715600B01
9	C016200A01	51	B000021C01
10	D425202A01	52	C715542B03
11	B000020A36	53	C715500A03
12	B000020A33	54	B000028E04
13	B000020A31	55	B000022A02
14	C425220A01	56	C715720G01
15	B000025A12	57	C715737A01
16	C425225A10	58	B000028E04
17	C425242A01	59	B000022A02
18	B000020A39	60	C620820K03
19	D425241A01	61	C620824A01
20	B000020A24	62	C650842A01
21	C225244A01	63	C715884A01
22	B000020A17	64	B000028E05
23	D416302A01	65	B000022A02
24	B000020A01	66	C620841A01
25	B000020A03	67	C715860A03
26	D715361A01	68	B000023B01
27	C216340A01	69	C715912A01
28	B000020A14	70	B000026A04
29	D425345A01	71	D715939G03
30	B000020A14	72	B000021C01
31	B000020A18	73	C430401A02
32	D416322A01	74	C620949A03
33	B000026A15	75	D425123A01
34	C425262A01	76	D425202A01
35	B000020A36	77	D425226A10
36	D425283A01	78	D425241A01
37	C715261A03	79	D416302A01
38	B000021C01	80	D715361A01
39	C420431B01	81	D425283A01
40	C620424A01	82	D715735G01
41	C420483B01	83	D715982G03
42	C715713A01	84	D715444A01

Codice **A715000H03**
Modello **M15 CL**
Tipo Punto **90**
Lungh. min. **10 mm.**
Lungh. max. **25 mm.**

Kode **A715000H03**
Modell **M15 CL**
Klammer Typ **90**
Min. Länge **10 mm.**
Max. Länge **25 mm.**

Code **A715000H03**
Model **M15 CL**
Staple type **90**
Min. length **10 mm.**
Max. length **25 mm.**

Code **A715000H03**
Modèle **M15 CL**
Agrafe type **90**
Longueur min. **10 mm.**
Longueur max. **25 mm.**

Código **A715000H03**
Modelo **M15 CL**
Grapa tipo **90**
Largueza min. **10 mm.**
Largueza max. **25 mm.**

Codigo **A715000H03**
Modelo **M15 CL**
Tipo de agrafe **90**
Largura min. **10 mm.**
Largura max. **25 mm.**

DATI TECNICI

Peso: **1010 gr.**
Dimensioni: **55-188-350 mm.**
Consumo aria: **0,49 NI/colpo (6 bar)**
Pressione min.: **4,0 bar**
Pressione max.: **7,0 bar**

TECHNISCHE DATEN

Gewicht: **1010 gr.**
Abmessungen: **55-188-350 mm.**
Luftverbrauch: **0,49 NI/pro Schlag (6 bar)**
Min.Betriebsdruck: **4,0 bar**
Max.Betriebsdruck: **7,0 bar**

TECHNICAL FEATURES

Weight: **1010 gr.**
Dimensions: **55-188-350 mm.**
Air consumption: **0,49 NI/shot (6 bar)**
Min.working pressure: **4,0 bar**
Max.working pressure: **7,0 bar**

DONNEES TECHNIQUES

Poids: **1010 gr.**
Dimensions: **55-188-350 mm.**
Consommation d'air: **0,49 NI/coup (6 bar)**
Pression de fonction min.: **4,0 bar**
Pression de fonction max.: **7,0 bar**

DATOS TECNICOS

Peso: **1010 gr.**
Dimensiones: **55-188-350 mm.**
Consumo de aire: **0,49 NI/disparo (6 bar)**
Presion min.: **4,0 bar**
Presion max.: **7,0 bar**

CARACTERISTICAS TECNICAS

Peso: **1010 gr.**
Dimensões: **55-188-350 mm.**
Consumo de ar: **0,49 NI/disparo (6 bar)**
Pressão min.: **4,0 bar**
Pressão max.: **7,0 bar**

POTENZA ACUSTICA

DIRETTIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

SCHALLEISTUNG

EWG RICHTLINIE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

NOISE POWER

EEC DIRECTIVE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

POTENCIA ACUSTICA

NORMATIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

POTENCIA ACUSTICA

DIRETTIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **81,2 (dB)**
LpA 60S 1M= **79,6 (dB)**

B615040A01 O-Ring Kit

VIBRAZIONI PRODOTTE

DIRETTIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inferiore a 2,5 (m/s²)**

GERAETEBOZGENER

VIBRATIONSWERT
EWG RICHTLINIE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **unter 2,5 (m/s²)**

TOOL RELATED VIBRATION

VALUE
EEC DIRECTIVE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **below 2,5 (m/s²)**

VALEUR DES VIBRATIONS

PAR LA MACHINE
DIRECTIVE CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inférieur à 2,5 (m/s²)**

VIBRACION PRODUCIDA

NORMATIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inferior a 2,5 (m/s²)**

NIVEL DE VIBRAÇÃO

DO PRODUTO
DIRETTIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **inferior a 2,5 (m/s²)**

715/0 H03/02 10/05