



**RIF. COD.**

1	B000028A12	43	C450180A01
2	C440101A01	44	B000028E02
3	C440103A01	45	C620768A01
4	B000028C04	46	B000023B02
5	C450180A01	47	D640707A01
6	D440123A01	48	B000028E14
7	C240160A01	49	B000021C01
8	B000020A06	50	D730484A01
9	C440181A01	51	B000026A09
10	B000020A43	52	B000028C05
11	D440202A01	53	B000028B23
12	B000020A40	54	C730681A01
13	B000020A39	55	C230661A01
14	D440204A01	56	C740600A01
15	B000020A44	57	C730540A05
16	B000023B05	58	C730912A05
17	B000020A52	59	B000028A03
18	C440220A01	60	C640822A01
19	C640225A09	61	C620736A01
20	B000020A60	62	D640735A01
21	D440241A02	63	C430401A02
22	B000020A40	64	C640937A09
23	C240244A01	65	B000026A21
24	B000020B02	66	B000021C01
25	B000020B01	67	C620948A05
26	B000020A02	68	C430401A02
27	D450304A01	69	C620949A01
28	B000020B11	70	C620820A01
29	B000020A02	71	C620824A01
30	D740361A01	72	C620842A01
31	B000020A19	73	C620884A01
32	B000020A19	74	C620860A05
33	B000026A12	75	D440123A01
34	D750411A02	76	D440202A01
35	C450262A01	77	D440204A01
36	B000020A42	78	D640226A09
37	D450283A01	79	D440241A02
38	C740261A01	80	D450304A01
39	C730500A01	81	D740361A01
40	D750441A01	82	D450283A01
41	B000026A09		
42	B000028B13		

Codice **A740000A10**  
Modello **M40**  
Tipo Punto **92**  
Lungh. min. **20 mm.**  
Lungh. max. **40 mm.**

Kode **A740000A10**  
Modell **M40**  
Klammer Typ **92**  
Min. Länge **20 mm.**  
Max. Länge **40 mm.**

Code **A740000A10**  
Model **M40**  
Staple type **92**  
Min. length **20 mm.**  
Max. length **40 mm.**

Code **A740000A10**  
Modèle **M40**  
Agrafe type **92**  
Longueur min. **20 mm.**  
Longueur max. **40 mm.**

Código **A740000A10**  
Modelo **M40**  
Grapa tipo **92**  
Largueza min. **20 mm.**  
Largueza max. **40 mm.**

Codigo **A740000A10**  
Modelo **M40**  
Tipo de agrafe **92**  
Largura min. **20 mm.**  
Largura max. **40 mm.**

**DATI TECNICI**

Peso: **1720 gr.**  
Dimensioni: **80-242-285 mm.**  
Consumo aria: **1,28 NI/colpo (6 bar)**  
Pressione min.: **4,0 bar**  
Pressione max.: **7,0 bar**

**TECHNISCHE DATEN**

Gewicht: **1720 gr.**  
Abmessungen: **80-242-285 mm.**  
Luftverbrauch: **1,28 NI/pro Schlag (6 bar)**  
Min.Betriebsdruck: **4,0 bar**  
Max.Betriebsdruck: **7,0 bar**

**TECHNICAL FEATURES**

Weight: **1720 gr.**  
Dimensions: **80-242-285 mm.**  
Air consumption: **1,28 NI/shot (6 bar)**  
Min.working pressure: **4,0 bar**  
Max.working pressure: **7,0 bar**

**DONNEES TECHNIQUES**

Poids: **1720 gr.**  
Dimensions: **80-242-285 mm.**  
Consommation d'air: **1,28 NI/coup (6 bar)**  
Pression de fonction min.: **4,0 bar**  
Pression de fonction max.: **7,0 bar**

**DATOS TECNICOS**

Peso: **1720 gr.**  
Dimensiones: **80-242-285 mm.**  
Consumo de aire: **1,28 NI/disparo (6 bar)**  
Presion min.: **4,0 bar**  
Presion max.: **7,0 bar**

**CARACTERISTICAS TECNICAS**

Peso: **1720 gr.**  
Dimensões: **80-242-285 mm.**  
Consumo de ar: **1,28 NI/disparo (6 bar)**  
Pressão min.: **4,0 bar**  
Pressão max.: **7,0 bar**

**POTENZA ACUSTICA**

DIRETTIVA CEE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **87,5 (dB)**  
LpA 60S 1M= **86,7 (dB)**

**SCHALLEISTUNG**

EWG RICHTLINIE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **87,5 (dB)**  
LpA 60S 1M= **86,7 (dB)**

**NOISE POWER**

EEC DIRECTIVE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **87,5 (dB)**  
LpA 60S 1M= **86,7 (dB)**

**PUISSANCE ACOUSTIQUE**

DIRECTIVE CEE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **87,5 (dB)**  
LpA 60S 1M= **86,7 (dB)**

**POTENCIA ACUSTICA**

NORMATIVA CEE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **87,5 (dB)**  
LpA 60S 1M= **86,7 (dB)**

**POTENCIA ACUSTICA**

DIRETTIVA CEE  
ISO-11148-13-2017  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **87,5 (dB)**  
LpA 60S 1M= **86,7 (dB)**

**B640040A01 O-Ring Kit**

**VIBRAZIONI PRODOTTE**

DIRETTIVA CEE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,6 (m/s²)**

**GERAETEBOZGENER VIBRATIONSWERT**

EWG RICHTLINIE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,6 (m/s²)**

**TOOL RELATED VIBRATION VALUE**

EEC DIRECTIVE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,6 (m/s²)**

**VALEUR DES VIBRATIONS PAR LA MACHINE**

DIRECTIVE CEE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,6 (m/s²)**

**VIBRACION PRODUCIDA**

NORMATIVA CEE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,6 (m/s²)**

**NIVEL DE VIBRAÇÃO DO PRODUTO**

DIRETTIVA CEE  
ISO-11148-13-2017  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,6 (m/s²)**

**740/0 A10/01 07/11**