


91



92

91 - ACCESSORIO PER GANCIO
HANGER ACCESSORY

92 - ACCESS. PER SOLO COLPO SINGOLO
ACCESSORY FOR ONLY SINGLE SHOT

RIF. COD.

1	B000028A24	43	D750441A01	85	D750243A01
2	C750104A01	44	B000026A11	86	D750226A01
3	B000020A04	45	B000028B12	87	D750241A01
4	C750100A01	46	C450180A01	88	D750304A01
5	C565103A01	47	B000020A17	89	D750361A01
6	B000028C07	48	C650737A01	90	D450283A01
7	C750180A01	49	C650701A01	91	C750105A01
8	D750123A01	50	B000021C01	92	C620408A01
9	B000020A37	51	D750484A01		
10	C750181A01	52	C750689A01		
11	C750200A01	53	B000022A01		
12	B000020A38	54	B000028E03		
13	B000020A44	55	B000026A11		
14	D750202A01	56	B000028B12		
15	B000020A42	57	C750681A02		
16	C750162A01	58	C230661A01		
17	C750246A03	59	C750600A03		
18	B000020A44	60	B000028B20		
19	D750243A01	61	C750507A01		
20	B000020A76	62	C750540A02		
21	B000021F01	63	C750912A01		
22	B000020A38	64	B000028A03		
23	D750226A01	65	C650736A01		
24	D750241A01	66	C650720A01		
25	B000020A43	67	C650937A01		
26	C450244A01	68	B000026A07		
27	B000020B02	69	B000021C01		
28	B000020B01	70	C650948A01		
29	D750304A01	71	B000022A02		
30	B000020A02	72	B000028E14		
31	B000020B11	73	C650710A01		
32	B000020A02	74	C430401A02		
33	D750361A01	75	C650949A01		
34	B000020A19	76	B000022A02		
35	B000020A19	77	B000028E05		
36	B000026A12	78	C620820A01		
37	D750411A02	79	C620824A01		
38	C450262A01	80	C650842A01		
39	B000020A42	81	C620884A01		
40	D450283A01	82	C650860A01		
41	C750261A01	83	D750123A01		
42	C750500A02	84	D750202A01		

Codice **A750000A02**

Modello **M50**
 Tipo Punto **16NC**
 Lungh. min. **25 mm.**
 Lungh. max. **50 mm.**

Kode **A750000A02**

Modell **M50**
 Klammer Typ **16NC**
 Min. Länge **25 mm.**
 Max. Länge **50 mm.**

Code **A750000A02**

Model **M50**
 Staple type **16NC**
 Min. length **25 mm.**
 Max. length **50 mm.**

Code **A750000A02**

Modèle **M50**
 Agrafe type **16NC**
 Longueur min. **25 mm.**
 Longueur max. **50 mm.**

Código **A750000A02**

Modelo **M50**
 Grapa tipo **16NC**
 Largueza min. **25 mm.**
 Largueza max. **50 mm.**

Codigo **A750000A02**

Modelo **M50**
 Tipo de agrafe **16NC**
 Largura min. **25 mm.**
 Largura max. **50 mm.**

DATI TECNICI

Peso: **2340 gr.**
 Dimensioni: **86-282-362 mm.**
 Consumo aria: **2,12 NI/colpo (6 bar)**
 Pressione min.: **5,0 bar**
 Pressione max.: **8,0 bar**

TECHNISCHE DATEN

Gewicht: **2340 gr.**
 Abmessungen: **86-282-362 mm.**
 Luftverbrauch: **2,12 NI/pro Schlag (6 bar)**
 Min.Betriebsdruck: **5,0 bar**
 Max.Betriebsdruck: **8,0 bar**

TECHNICAL FEATURES

Weight: **2340 gr.**
 Dimensions: **86-282-362 mm.**
 Air consumption: **2,12 NI/shot (6 bar)**
 Min.working pressure: **5,0 bar**
 Max.working pressure: **8,0 bar**

DONNEES TECHNIQUES

Poids: **2340 gr.**
 Dimensions: **86-282-362 mm.**
 Consommation d'air: **2,12 NI/coup (6 bar)**
 Pression de fonction min.: **5,0 bar**
 Pression de fonction max.: **8,0 bar**

DATOS TECNICOS

Peso: **2340 gr.**
 Dimensiones: **86-282-362 mm.**
 Consumo de aire: **2,12 NI/disparo (6 bar)**
 Presion min.: **5,0 bar**
 Presion max.: **8,0 bar**

CARACTERISTICAS TECNICAS

Peso: **2340 gr.**
 Dimensões: **86-282-362 mm.**
 Consumo de ar: **2,12 NI/disparo (6 bar)**
 Pressão min.: **5,0 bar**
 Pressão max.: **8,0 bar**

POTENZA ACUSTICA

DIRETTIVA CEE
 ISO-11148-13-2017
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **89,5 (dB)**
 LpA 60S 1M= **82,1 (dB)**

SCHALLEISTUNG

EWG RICHTLINIE
 ISO-11148-13-2017
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **89,5 (dB)**
 LpA 60S 1M= **82,1 (dB)**

NOISE POWER

EEC DIRECTIVE
 ISO-11148-13-2017
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **89,5 (dB)**
 LpA 60S 1M= **82,1 (dB)**

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE
 ISO-11148-13-2017
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **89,5 (dB)**
 LpA 60S 1M= **82,1 (dB)**

POTENCIA ACUSTICA

NORMATIVA CEE
 ISO-11148-13-2017
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **89,5 (dB)**
 LpA 60S 1M= **82,1 (dB)**

POTENCIA ACUSTICA

DIRETTIVA CEE
 ISO-11148-13-2017
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **89,5 (dB)**
 LpA 60S 1M= **82,1 (dB)**

B750040A01 O-Ring Kit**VIBRAZIONI PRODOTTE**

DIRETTIVA CEE
 ISO-11148-13-2017
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **2,8 (m/s²)**

GERAETEBOZGENER

VIBRATIONS WERT
 EWG RICHTLINIE
 ISO-11148-13-2017
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **2,8 (m/s²)**

TOOL RELATED VIBRATION

VALUE
 EEC DIRECTIVE
 ISO-11148-13-2017
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **2,8 (m/s²)**

VALEUR DES VIBRATIONS

PAR LA MACHINE
 DIRECTIVE CEE
 ISO-11148-13-2017
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **2,8 (m/s²)**

VIBRACION PRODUCIDA

NORMATIVA CEE
 ISO-11148-13-2017
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **2,8 (m/s²)**

NIVEL DE VIBRACAO

DO PRODUTO
 DIRETTIVA CEE
 ISO-11148-13-2017
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **2,8 (m/s²)**

750/0 A02/01 08/02