



**RIF. COD.**

1	B000028A24	43	B000028B19	85	D790325F01
2	C750104A01	44	D790600F01	86	C790271F01
3	B000020A04	45	C790540F01	87	C750270A01
4	C750100A01	46	C790912F01	88	B000028B12
5	C790103U01	47	B000026A08		
6	B000028C12	48	D790937F01		
7	C750180A01	49	B000026A06		
8	D790123K02	50	B000028B24		
9	B000020A37	51	B000028B24		
10	C565181A01	52	B000028B24		
11	C750200A01	53	C790720F01		
12	B000020A38	54	B000028B20		
13	B000020A44	55	C565180A01		
14	D790202U01	56	C565689A01		
15	B000020A43	57	D790484F01		
16	C750162A01	58	B000026A15		
17	D790242F01	59	D790441U01		
18	B000020A49	60	B000026A15		
19	C770222U01	61	D790871F01		
20	C790220F01	62	B000028E02		
21	B000020B43	63	C275843K01		
22	C790225F01	64	B000026A04		
23	D790241F01	65	B000020A48		
24	B000020A49	66	D465283A01		
25	B000020A47	67	B000020A67		
26	B000020A56	68	D790300F01		
27	D790243F01	69	B000020A20		
28	C790244F01	70	C430401A02		
29	C790261U02	71	B000020A17		
30	D790265A01	72	D790345F01		
31	B000023A06	73	B000020A15		
32	C790528U01	74	B000020A73		
33	C790525F01	75	D790325F01		
34	B000022C04	76	D790123K02		
35	B000028B42	77	D790202U01		
36	C790500F01	78	D790242F01		
37	C710842U03	79	D790226F01		
38	C790681F01	80	D790241F01		
39	B000028B20	81	D790243F01		
40	C790662F01	82	D465283A01		
41	B000022D11	83	D790300F01		
42	B000028B11	84	D790345F01		

Codice **A790000F01**  
 Modello **M90**  
 Tipo Punto **FENCING 4.0**  
 Lunghezza min. **25 mm.**  
 Lunghezza max. **50 mm.**

Kode **A790000F01**  
 Modell **M90**  
 Klammer Typ **FENCING 4.0**  
 Min. Länge **25 mm.**  
 Max. Länge **50 mm.**

Code **A790000F01**  
 Model **M90**  
 Staple type **FENCING 4.0**  
 Min. length **25 mm.**  
 Max. length **50 mm.**

Code **A790000F01**  
 Modèle **M90**  
 Agrafe type **FENCING 4.0**  
 Longueur min. **25 mm.**  
 Longueur max. **50 mm.**

Código **A790000F01**  
 Modelo **M90**  
 Grapa tipo **FENCING 4.0**  
 Largueza min. **25 mm.**  
 Largueza max. **50 mm.**

Codigo **A790000F01**  
 Modelo **M90**  
 Tipo de agrafe **FENCING 4.0**  
 Largura min. **25 mm.**  
 Largura max. **50 mm.**

**DATI TECNICI**

Peso: **4300 gr.**  
 Dimensioni: **95-360-370 mm.**  
 Consumo aria: **3,50 NI/colpo**  
 Pressione min.: **5,0 bar**  
 Pressione max.: **8,0 bar**

**TECHNISCHE DATEN**

Gewicht: **4300 gr.**  
 Abmessungen: **95-360-370 mm**  
 Luftverbrauch: **3,50 NI/pro Sch**  
 Min.Betriebsdruck: **5,0 bar**  
 Max.Betriebsdruck: **8,0 bar**

**TECHNICAL FEATURES**

Weight: **4300 gr.**  
 Dimensions: **95-360-370 mm.**  
 Air consumption: **3,50 NI/shot**  
 Min.working pressure: **5,0 bar**  
 Max.working pressure: **8,0 bar**

**DONNEES TECHNIQUES**

Poids: **4300 gr.**  
 Dimensions: **95-360-370 mm.**  
 Consommation d'air: **3,50 NI/c**  
 Pression de fonction min.: **5,0 I**  
 Pression de fonction max.: **8,0**

**DATOS TECNICOS**

Peso: **4300 gr.**  
 Dimensiones: **95-360-370 mm.**  
 Consumo de aire: **3,50 NI/disp**  
 Presion min.: **5,0 bar**  
 Presion max.: **8,0 bar**

**CARACTERISTICAS TECNIC**

Peso: **4300 gr.**  
 Dimensões: **95-360-370 mm.**  
 Consumo de ar: **3,50 NI/dispai**  
 Pressão min.: **5,0 bar**  
 Pressão max.: **8,0 bar**

**POTENZA ACUSTICA**

DIRETTIVA CEE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **94,7 (dB)**  
 LpA 60S 1M= **93,8 (dB)**

**SCHALLEISTUNG**

EWG RICHTLINIE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **94,7 (dB)**  
 LpA 60S 1M= **93,8 (dB)**

**NOISE POWER**

EEC DIRECTIVE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **94,7 (dB)**  
 LpA 60S 1M= **93,8 (dB)**

**PUISSANCE ACOUSTIQUE**

DIRECTIVE CEE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **94,7 (dB)**  
 LpA 60S 1M= **93,8 (dB)**

**POTENCIA ACUSTICA**

NORMATIVA CEE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **94,7 (dB)**  
 LpA 60S 1M= **93,8 (dB)**

**POTENCIA ACUSTICA**

DIRETTIVA CEE  
 ISO-11148-13-2017  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **94,7 (dB)**  
 LpA 60S 1M= **93,8 (dB)**

**B790040F01 O-Ring Kit**

**VIBRAZIONI PRODOTTE**

DIRETTIVA CEE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= **4,2 (m/s²)**

**GERAETEBEZOGENER VIBRATIONS WERT**

EWG RICHTLINIE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= **4,2 (m/s²)**

**TOOL RELATED VIBRATION VALUE**

EEC DIRECTIVE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= **4,2 (m/s²)**

**VALEUR DES VIBRATIONS PAR LA MACHINE**

DIRECTIVE CEE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= **4,2 (m/s²)**

**VIBRACION PRODUCIDA**

NORMATIVA CEE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= **4,2 (m/s²)**

**NIVEL DE VIBRAÇÃO DO PRODUTO**

DIRETTIVA CEE  
 ISO-11148-13-2017  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= **4,2 (m/s²)**

**790/0 F01/01 03/21**