



<u>RIF.</u>	<u>COD.</u>			<u>DATI TECNICI</u>	<u>POTENZA ACUSTICA</u>	<u>VIBRAZIONI PRODOTTE</u>
1	B000028A04	40	C416261A02	Codice A610000B03 Modello ML10 SIC	Peso: 850 gr. Dimensioni: 44-155-222 mm.	DIRETTIVA 89/392 CEE ISO/FDIS 8662-11 (1999)
2	C416100A01	41	C016483B01	Tipo Punto 50	Consumo aria: 0,24 NI/colpo (6 bar)	ah.w.3s= inferiore a 2,5 (m/s²)
3	C416103A02	42	B000028B06	Lungh. min. 6 mm.	Pressione min.: 4,0 bar	
4	D416123A01	43	B000028B01	Lungh. max. 16 mm.	Pressione max.: 7,0 bar	
5	B000020A36	44	C416681B01			
6	C216160A01	45	C216661B01			
7	B000020A19	46	C610600B01	Kode A610000B03	<u>TECHNISCHE DATEN</u> Gewicht: 850 gr.	<u>SCHALLEISTUNG</u> EWG RICHTLINIE 89/392
8	C016200A01	47	B000021C01	Modell ML10 SIC	Abmessungen: 44-155-222 mm.	prEN 12549 (1999)
9	D416202A02	48	B000028B04	Klammer Typ 50	Luftverbrauch: 0,24 NI/pro Schlag (6 bar)	UNI EN ISO 3744 (1997)
10	B000020A35	49	C610542B05	Min. Länge 6 mm.	Min.Betriebsdruck: 4,0 bar	LwA= 80,3 (dB)
11	B000020A31	50	C416500A01	Max. Länge 16 mm.	Max.Betriebsdruck: 7,0 bar	LpA 60S 1M= 78,9 (dB)
12	C416220A01	51	C416722A02			
13	B000025A06	52	B000021C01			
14	C610225A05	53	C216424A01	Code A610000B03	<u>TECHNICAL FEATURES</u> Weight: 850 gr.	<u>NOISE POWER</u> EEC DIRECTIVE 89/392
15	B000020A29	54	B000028A04	Model ML10 SIC	Dimensions: 44-155-222 mm.	prEN 12549 (1999)
16	D416241A02	55	C416990A01	Staple type 50	Air consumption: 0,24 NI/shot (6 bar)	UNI EN ISO 3744 (1997)
17	B000020A35	56	B000021C01	Min. length 6 mm.	Min.working pressure: 4,0 bar	LwA= 80,3 (dB)
18	B000020A22	57	B000028A06	Max. length 16 mm.	Max.working pressure: 7,0 bar	LpA 60S 1M= 78,9 (dB)
19	C016244A01	58	B000023B02			
20	B000020A17	59	C416763A01			
21	D416302A01	60	B000026A05	Code A610000B03	<u>DONNEES TECHNIQUES</u> Poids: 850 gr.	<u>PUISSANCE ACOUSTIQUE</u> DIRECTIVE CEE 89/392
22	B000020A01	61	D416984A63	Modèle ML10 SIC	Dimensions: 44-155-222 mm.	prEN 12549 (1999)
23	B000020A03	62	C416860A02	Agrafe type 50	Consommation d'air: 0,24 NI/coup (6 bar)	UNI EN ISO 3744 (1997)
24	D416361A01	63	C216842A01	Longueur min. 6 mm.	Pression de fonction min.: 4,0 bar	LwA= 80,3 (dB)
25	C216340A01	64	C225884A01	Longueur max. 16 mm.	Pression de fonction max.: 7,0 bar	LpA 60S 1M= 78,9 (dB)
26	B000020A14	65	D416123A01			
27	D416345A01	66	D416202A02			
28	B000020A14	67	D610226A05	Código A610000B03	<u>DATOS TECNICOS</u> Peso: 850 gr.	<u>POTENCIA ACUSTICA</u> NORMATIVA 89/392 CEE
29	B000020A18	68	D416241A02	Modelo ML10 SIC	Dimensiones: 44-155-222 mm.	prEN 12549 (1999)
30	D416322A01	69	D416302A01	Grapa tipo 50	Consumo de aire: 0,24 NI/disparo (6 bar)	UNI EN ISO 3744 (1997)
31	C416431B01	70	D416361A01	Largura min. 6 mm.	Presion min.: 4,0 bar	LwA= 80,3 (dB)
32	C425262A01	71	D216283A01	Largura max. 16 mm.	Presion max.: 7,0 bar	LpA 60S 1M= 78,9 (dB)
33	B000027B03	72	D416984A63			
34	B000026A08					
35	B000020A36			Codigo A610000B03	<u>CARACTERISTICAS TECNICAS</u> Peso: 850 gr.	<u>POTENCIA ACUSTICA</u> DIRECTIVA 89/392 CEE
36	D216283A01			Modelo ML10 SIC	Dimensões: 44-155-222 mm.	prEN 12549 (1999)
37	C416764A01			Tipo de agrafe 50	Consumo de ar: 0,24 NI/disparo (6 bar)	UNI EN ISO 3744 (1997)
38	C016761A01			Largura min. 6 mm.	Pressão min.: 4,0 bar	LwA= 80,3 (dB)
39	C416760A01			Largura max. 16 mm.	Pressão max.: 7,0 bar	LpA 60S 1M= 78,9 (dB)
						<u>GERAETEBEZOGENER VIBRATIONSWERT</u> EWG RICHTLINIE 89/392 ISO/FDIS 8662-11 (1999) ah.w.3s= unter 2,5 (m/s²)
						<u>TOOL RELATED VIBRATION VALUE</u> EEC DIRECTIVE 89/392 ISO/FDIS 8662-11 (1999) ah.w.3s= below 2,5 (m/s²)
						<u>VALEUR DES VIBRATIONS PAR LA MACHINE</u> DIRECTIVE CEE 89/392 ISO/FDIS 8662-11 (1999) ah.w.3s= inférieur á 2,5 (m/s²)
						<u>VIBRACION PRODUCIDA</u> NORMATIVA 89/392 CEE ISO/FDIS 8662-11 (1999) ah.w.3s= inferior a 2,5 (m/s²)
						<u>NIVEL DE VIBRACAO DO PRODUTO</u> DIRECTIVA 89/392 CEE ISO/FDIS 8662-11 (1999) ah.w.3s= inferior a 2,5 (m/s²)

B610040A01 O-Ring Kit

610/0 B03/01 02/04