



RIF. COD.

1	B000028A04	43	B000020A03
2	C416100A01	44	C416262A01
3	D416123A03	45	C216420A01
4	B000020A36	46	B000026A08
5	C216160A01	47	B000020A36
6	B000020A19	48	D216283A01
7	C016200A01	49	C416764A01
8	D416202A02	50	B000023B02
9	B000020A35	51	B000028B05
10	B000020A31	52	B000022A01
11	C416220A01	53	C416540A63
12	B000025A06	54	C416500A02
13	C416225A63	55	C416722A02
14	B000020A29	56	B000023B01
15	D416241A02	57	D416427A01
16	B000020A35	58	B000028A04
17	B000020A22	59	C416990A01
18	C416244A02	60	B000028A06
19	D416350A02	61	C016761A01
20	B000020A14	62	B000021C01
21	D416261A02	63	C416760A01
22	B000021C01	64	C416763A01
23	B000020A15	65	B000026A05
24	B000020A62	66	D416984A63
25	D416364A01	67	C416860A02
26	C416352A01	68	C216842A01
27	C416351A01	69	C225884A01
28	B000020A16	70	D416123A03
29	B000020A16	71	D416202A02
30	D416304A01	72	D416226A63
31	B000020A62	73	D416241A02
32	C416306A01	74	D416350A02
33	B000020A15	75	D416364A01
34	D416325A01	76	D416304A01
35	B000020A19	77	D416325A01
36	C216340A01	78	D416345A02
37	B000020A14	79	D416322A02
38	B000020A14	80	D216283A01
39	D416345A02	81	D416984A63
40	B000020A14		
41	B000020A63		
42	D416322A02		

Codice **A610003A03**
Modello **ML10 AUTO**
Tipo Punto **64**
Lungh. min. **6 mm.**
Lungh. max. **16 mm.**

Kode **A610003A03**
Modell **ML10 AUTO**
Klammer Typ **64**
Min. Länge **6 mm.**
Max. Länge **16 mm.**

Code **A610003A03**
Model **ML10 AUTO**
Staple type **64**
Min. length **6 mm.**
Max. length **16 mm.**

Code **A610003A03**
Modèle **ML10 AUTO**
Agrafe type **64**
Longueur min. **6 mm.**
Longueur max. **16 mm.**

Código **A610003A03**
Modelo **ML10 AUTO**
Grapa tipo **64**
Largueza min. **6 mm.**
Largueza max. **16 mm.**

Código **A610003A03**
Modelo **ML10 AUTO**
Tipo de agrafe **64**
Largura min. **6 mm.**
Largura max. **16 mm.**

DATI TECNICI

Peso: **860 gr.**
Dimensioni: **48-155-222 mm.**
Consumo aria: **0,25 NI/colpo (6 bar)**
Pressione min.: **4,0 bar**
Pressione max.: **7,0 bar**

TECHNISCHE DATEN

Gewicht: **860 gr.**
Abmessungen: **48-155-222 mm.**
Luftverbrauch: **0,25 NI/pro Schlag (6 bar)**
Min.Betriebsdruck: **4,0 bar**
Max.Betriebsdruck: **7,0 bar**

TECHNICAL FEATURES

Weight: **860 gr.**
Dimensions: **48-155-222 mm.**
Air consumption: **0,25 NI/shot (6 bar)**
Min.working pressure: **4,0 bar**
Max.working pressure: **7,0 bar**

DONNEES TECHNIQUES

Poids: **860 gr.**
Dimensions: **48-155-222 mm.**
Consommation d'air: **0,25 NI/coup (6 bar)**
Pression de fonction min.: **4,0 bar**
Pression de fonction max.: **7,0 bar**

DATOS TECNICOS

Peso: **860 gr.**
Dimensiones: **48-155-222 mm.**
Consumo de aire: **0,25 NI/disparo (6 bar)**
Presion min.: **4,0 bar**
Presion max.: **7,0 bar**

CARACTERISTICAS TECNICAS

Peso: **860 gr.**
Dimensões: **48-155-222 mm.**
Consumo de ar: **0,25 NI/disparo (6 bar)**
Pressão min.: **4,0 bar**
Pressão max.: **7,0 bar**

POTENZA ACUSTICA

DIRETTIVA 89/392 CEE
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **102,1 (dB)**
LpA 60S 1M= **99,8 (dB)**

SCHALLEISTUNG

EWG RICHTLINIE 89/392
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **102,1 (dB)**
LpA 60S 1M= **99,8 (dB)**

NOISE POWER

EEC DIRECTIVE 89/392
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **102,1 (dB)**
LpA 60S 1M= **99,8 (dB)**

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE 89/392
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **102,1 (dB)**
LpA 60S 1M= **99,8 (dB)**

POTENCIA ACUSTICA

NORMATIVA 89/392 CEE
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **102,1 (dB)**
LpA 60S 1M= **99,8 (dB)**

POTENCIA ACUSTICA

DIRETTIVA 89/392 CEE
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **102,1 (dB)**
LpA 60S 1M= **99,8 (dB)**

B610040A03 O-Ring Kit

VIBRAZIONI PRODOTTE

DIRETTIVA 89/392 CEE
ISO/FDIS 8662-11 (1999)
ah.w.3s= inferiore a **2,5 (m/s²)**

GERAETEBEZOGENER VIBRATIONSWERT

EWG RICHTLINIE 89/392
ISO/FDIS 8662-11 (1999)
ah.w.3s= unter **2,5 (m/s²)**

TOOL RELATED VIBRATION VALUE

EEC DIRECTIVE 89/392
ISO/FDIS 8662-11 (1999)
ah.w.3s= below **2,5 (m/s²)**

VALEUR DES VIBRATIONS PAR LA MACHINE

DIRECTIVE CEE 89/392
ISO/FDIS 8662-11 (1999)
ah.w.3s= inférieur à **2,5 (m/s²)**

VIBRACION PRODUCIDA

NORMATIVA 89/392 CEE
ISO/FDIS 8662-11 (1999)
ah.w.3s= inferior a **2,5 (m/s²)**

NIVEL DE VIBRAÇÃO DO PRODUTO

DIRETTIVA 89/392 CEE
ISO/FDIS 8662-11 (1999)
ah.w.3s= inferior a **2,5 (m/s²)**

610/3 A03/01 02/04