



RIF. COD.

1	B000028A10	43	D715361A01
2	C425100A01	44	C216340A01
3	D428123D02	45	B000020A14
4	B000020A40	46	D425345A01
5	B000020A39	47	B000020A14
6	C225160A01	48	B000020A18
7	B000020A04	49	D416322A01
8	C016200A01	50	D425442B01
9	D428202D01	51	C620424A01
10	B000020A36	52	B000026A15
11	B000020A33	53	B000021C01
12	B000023B05	54	B000020A36
13	B000020A31	55	D425283A01
14	C428220D01	56	B000023B02
15	C428225D02	57	C228860A03
16	C425242A01	58	C228841A01
17	B000020A39	59	D428984D02
18	D428241D01	60	C216842A02
19	B000020A24	61	C228840A01
20	C225244A01	62	B000027A05
21	C618261A01	63	D425441B02
22	B000028B07	64	C425403B02
23	C228681A01	65	C230405A01
24	C216661B01	66	C620424A01
25	C428600D01	67	B000021C01
26	B000021C01	68	C425486B01
27	B000028A02	69	C425487B01
28	D428546D02	70	D425484B01
29	C618500D01	71	D428123D02
30	C228483A01	72	D428202D01
31	C428722A04	73	D428226D02
32	B000028A06	74	D428241D01
33	C428987A01	75	D416302A01
34	C016761A01	76	D715361A01
35	C425760A02	77	D425283A01
36	C416763A01	78	D425441B02
37	B000021C01	79	D425484B01
38	B000026A05	80	D425444B02
39	B000020A17	81	D428984D02
40	D416302A01	82	B000028A03
41	B000020A01	83	C416990A02
42	B000020A03		

Codice **A618000D03**Modello **ML18 BL50**Tipo Punto **90**Lungh. min. **15 mm.**Lungh. max. **32 mm.**Kode **A618000D03**Modell **ML18 BL50**Klammer Typ **90**Min. Länge **15 mm.**Max. Länge **32 mm.**Code **A618000D03**Model **ML18 BL50**Staple type **90**Min. length **15 mm.**Max. length **32 mm.**Code **A618000D03**Modèle **ML18 BL50**Agrafe type **90**Longueur min. **15 mm.**Longueur max. **32 mm.**Código **A618000D03**Modelo **ML18 BL50**Grapa tipo **90**Largueza min. **15 mm.**Largueza max. **32 mm.**Codigo **A618000D03**Modelo **ML18 BL50**Tipo de agrafe **90**Largura min. **15 mm.**Largura max. **32 mm.****DATI TECNICI**Peso: **1280 gr.**Dimensioni: **55-254-222 mm.**Consumo aria: **0,63 NI/colpo (6 bar)**Pressione min.: **4,0 bar**Pressione max.: **7,0 bar****TECHNISCHE DATEN**Gewicht: **1280 gr.**Abmessungen: **55-254-222 mm.**Luftverbrauch: **0,63 NI/pro Schlag (6 bar)**Min.Betriebsdruck: **4,0 bar**Max.Betriebsdruck: **7,0 bar****TECHNICAL FEATURES**Weight: **1280 gr.**Dimensions: **55-254-222 mm.**Air consumption: **0,63 NI/shot (6 bar)**Min.working pressure: **4,0 bar**Max.working pressure: **7,0 bar****DONNEES TECHNIQUES**Poids: **1280 gr.**Dimensions: **55-254-222 mm.**Consommation d'air: **0,63 NI/coup (6 bar)**Pression de fonction min.: **4,0 bar**Pression de fonction max.: **7,0 bar****DATOS TECNICOS**Peso: **1280 gr.**Dimensiones: **55-254-222 mm.**Consumo de aire: **0,63 NI/disparo (6 bar)**Presion min.: **4,0 bar**Presion max.: **7,0 bar****CARACTERISTICAS TECNICAS**Peso: **1280 gr.**Dimensões: **55-254-222 mm.**Consumo de ar: **0,63 NI/disparo (6 bar)**Pressão min.: **4,0 bar**Pressão max.: **7,0 bar****POTENZA ACUSTICA**

DIRETTIVA 89/392 CEE

prEN 12549 (1999)

UNI EN ISO 3744 (1997)

LwA= **82,3 (dB)**LpA 60S 1M= **80,5 (dB)****SCHALLEISTUNG**

EWG RICHTLINIE 89/392

prEN 12549 (1999)

UNI EN ISO 3744 (1997)

LwA= **82,3 (dB)**LpA 60S 1M= **80,5 (dB)****NOISE POWER**

EEC DIRECTIVE 89/392

prEN 12549 (1999)

UNI EN ISO 3744 (1997)

LwA= **82,3 (dB)**LpA 60S 1M= **80,5 (dB)****PUISSANCE ACOUSTIQUE**

DIRECTIVE CEE 89/392

prEN 12549 (1999)

UNI EN ISO 3744 (1997)

LwA= **82,3 (dB)**LpA 60S 1M= **80,5 (dB)****POTENCIA ACUSTICA**

NORMATIVA 89/392 CEE

prEN 12549 (1999)

UNI EN ISO 3744 (1997)

LwA= **82,3 (dB)**LpA 60S 1M= **80,5 (dB)****POTENCIA ACUSTICA**

DIRECTIVA 89/392 CEE

prEN 12549 (1999)

UNI EN ISO 3744 (1997)

LwA= **82,3 (dB)**LpA 60S 1M= **80,5 (dB)****B618040D01 O-Ring Kit****VIBRAZIONI PRODOTTE**

DIRETTIVA 89/392 CEE

ISO/FDIS 8662-11 (1999)

ah.w.3s= inferiore a **2,5 (m/s²)****GERAETEBEZOGENER****VIBRATIONSWERT**

EWG RICHTLINIE 89/392

ISO/FDIS 8662-11 (1999)

ah.w.3s= unter **2,5 (m/s²)****TOOL RELATED VIBRATION****VALUE**

EEC DIRECTIVE 89/392

ISO/FDIS 8662-11 (1999)

ah.w.3s= below **2,5 (m/s²)****VALEUR DES VIBRATIONS****PAR LA MACHINE**

DIRECTIVE CEE 89/392

ISO/FDIS 8662-11 (1999)

ah.w.3s= inférieur á **2,5 (m/s²)****VIBRACION PRODUCIDA**

NORMATIVA 89/392 CEE

ISO/FDIS 8662-11 (1999)

ah.w.3s= inferior a **2,5 (m/s²)****NIVEL DE VIBRAÇÃO****DO PRODUTO**

DIRECTIVA 89/392 CEE

ISO/FDIS 8662-11 (1999)

ah.w.3s= inferior a **2,5 (m/s²)****618/0 D03/03 04/10**