



RIF. COD.

| | | | |
|----|------------|----|------------|
| 1 | B000028A10 | 43 | D428871M01 |
| 2 | C425100A01 | 44 | C216840K01 |
| 3 | D425123A01 | 45 | D428989N02 |
| 4 | B000020A40 | 46 | C216842A02 |
| 5 | B000020A39 | 47 | C216967K01 |
| 6 | C225160A01 | 48 | B000028A03 |
| 7 | B000020A04 | 49 | B000020A17 |
| 8 | C016200A01 | 50 | D416302A01 |
| 9 | D425202A01 | 51 | B000020A01 |
| 10 | B000020A36 | 52 | B000020A03 |
| 11 | B000020A33 | 53 | D715361A01 |
| 12 | C425220A01 | 54 | C216340A01 |
| 13 | B000026A12 | 55 | B000020A14 |
| 14 | C428225M03 | 56 | D425345A01 |
| 15 | B000020A31 | 57 | B000020A14 |
| 16 | C425242A01 | 58 | B000020A18 |
| 17 | D425241A01 | 59 | D416322A01 |
| 18 | B000020A39 | 60 | C425431B01 |
| 19 | B000020A24 | 61 | B000026A15 |
| 20 | C428244A01 | 62 | C620424A01 |
| 21 | C618261A01 | 63 | B000021C01 |
| 22 | B000028B07 | 64 | B000020A36 |
| 23 | C225681B01 | 65 | D425283A01 |
| 24 | C216661B01 | 66 | B000023B02 |
| 25 | C225600B01 | 67 | C425740K01 |
| 26 | B000021C01 | 68 | C428743M02 |
| 27 | B000028A02 | 69 | C428744M02 |
| 28 | C428542N01 | 70 | C216746M01 |
| 29 | C228500A01 | 71 | D425123A01 |
| 30 | C228483A01 | 72 | D425202A01 |
| 31 | B000028A06 | 73 | D428226M03 |
| 32 | B000028A03 | 74 | D425241A01 |
| 33 | C416990M02 | 75 | D416302A01 |
| 34 | C428722M04 | 76 | D715361A01 |
| 35 | B000028A06 | 77 | D425283A01 |
| 36 | B000020A18 | 78 | D428989N02 |
| 37 | C425748M01 | | |
| 38 | C016761A01 | | |
| 39 | C425760A02 | | |
| 40 | C416763A01 | | |
| 41 | B000021C01 | | |
| 42 | B000026A05 | | |

Codice A618000N01
Modello ML18
Tipo Punto I
Lungh. min. 20 mm.
Lungh. max. 30 mm.

Kode A618000N01
Modell ML18
Klammer Typ I
Min. Länge 20 mm.
Max. Länge 30 mm.

Code A618000N01
Model ML18
Staple type I
Min. length 20 mm.
Max. length 30 mm.

Code A618000N01
Modèle ML18
Agrafe type I
Longueur min. 20 mm.
Longueur max. 30 mm.

Código A618000N01
Modelo ML18
Grapa tipo I
Largueza min. 20 mm.
Largueza max. 30 mm.

Codigo A618000N01
Modelo ML18
Tipo de agrafe I
Largura min. 20 mm.
Largura max. 30 mm.

DATI TECNICI

Peso: 1320 gr.
Dimensioni: 55-188-222 mm.
Consumo aria: 0,49 NI/colpo (6 bar)
Pressione min.: 4,0 bar
Pressione max.: 7,0 bar

TECHNISCHE DATEN

Gewicht: 1320 gr.
Abmessungen: 55-188-222 mm.
Luftverbrauch: 0,49 NI/pro Schlag (6 bar)
Min.Betriebsdruck: 4,0 bar
Max.Betriebsdruck: 7,0 bar

TECHNICAL FEATURES

Weight: 1320 gr.
Dimensions: 55-188-222 mm.
Air consumption: 0,49 NI/shot (6 bar)
Min.working pressure: 4,0 bar
Max.working pressure: 7,0 bar

DONNEES TECHNIQUES

Poids: 1320 gr.
Dimensions: 55-188-222 mm.
Consommation d'air: 0,49 NI/coup (6 bar)
Pression de fonction min.: 4,0 bar
Pression de fonction max.: 7,0 bar

DATOS TECNICOS

Peso: 1320 gr.
Dimensiones: 55-188-222 mm.
Consumo de aire: 0,49 NI/disparo (6 bar)
Presion min.: 4,0 bar
Presion max.: 7,0 bar

CARACTERISTICAS TECNICAS

Peso: 1320 gr.
Dimensões: 55-188-222 mm.
Consumo de ar: 0,49 NI/disparo (6 bar)
Pressão min.: 4,0 bar
Pressão max.: 7,0 bar

POTENZA ACUSTICA

DIRETTIVA 89/392 CEE
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 81,2 (dB)
LpA 60S 1M= 79,6 (dB)

SCHALLEISTUNG

EWG RICHTLINIE 89/392
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 81,2 (dB)
LpA 60S 1M= 79,6 (dB)

NOISE POWER

EEC DIRECTIVE 89/392
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 81,2 (dB)
LpA 60S 1M= 79,6 (dB)

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE 89/392
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 81,2 (dB)
LpA 60S 1M= 79,6 (dB)

POTENCIA ACUSTICA

NORMATIVA 89/392 CEE
NORMATIVA 89/392 CEE
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 81,2 (dB)
LpA 60S 1M= 79,6 (dB)

POTENCIA ACUSTICA

DIRETTIVA 89/392 CEE
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 81,2 (dB)
LpA 60S 1M= 79,6 (dB)

VIBRAZIONI PRODOTTE

DIRETTIVA 89/392 CEE
ISO/FDIS 8662-11 (1999)
ah.w.3s= inferiore a 2,5 (m/s²)

GERAETEBEZOGENER VIBRATIONSWERT

EWG RICHTLINIE 89/392
ISO/FDIS 8662-11 (1999)
ah.w.3s= unter 2,5 (m/s²)

TOOL RELATED VIBRATION VALUE

EEC DIRECTIVE 89/392
ISO/FDIS 8662-11 (1999)
ah.w.3s= below 2,5 (m/s²)

VALEUR DES VIBRATIONS PAR LA MACHINE

DIRECTIVE CEE 89/392
ISO/FDIS 8662-11 (1999)
ah.w.3s= inférieur à 2,5 (m/s²)

VIBRACION PRODUCIDA

NORMATIVA 89/392 CEE
NORMATIVA 89/392 CEE
ISO/FDIS 8662-11 (1999)
ah.w.3s= inferior a 2,5 (m/s²)

NIVEL DE VIBRACAO DO PRODUTO

DIRETTIVA 89/392 CEE
ISO/FDIS 8662-11 (1999)
ah.w.3s= inferior a 2,5 (m/s²)

B615040A01 O-Ring Kit

618/0 N01/03 04/10