



**RIF. COD.**

1 B000028A10 43 C620503A09  
 2 C425100A01 44 C620500A01  
 3 C425103A02 45 B000028C04  
 4 D428123M01 46 B000022A01  
 5 B000020A40 47 B000028E03  
 6 B000020A39 48 B000021C01  
 7 C225160A01 49 D450441A01  
 8 B000020A04 50 C620424A01  
 9 C016200A01 51 B000028E14  
 10 D425202A01 52 B000022A02  
 11 B000020A36 53 B000028E02  
 12 B000020A33 54 C620768A01  
 13 B000020A31 55 B000023B02  
 14 C425220A01 56 C620701A01  
 15 B000025A12 57 B000028E14  
 16 C620225A09 58 C620697A01  
 17 C425242A01 59 B000021C03  
 18 B000020A39 60 C620699A01  
 19 D620241A01 61 C620698A03  
 20 B000020A24 62 C620684A01  
 21 C225244A01 63 C620600A01  
 22 B000020A17 64 B000021C03  
 23 D416302A01 65 C620551A01  
 24 B000020A01 66 C620524A01  
 25 B000020A03 67 D620670A01  
 26 D620361A01 68 C620540A09  
 27 C216340A01 69 B000028A03  
 28 B000020A14 70 C620822A01  
 29 D620345A01 71 C620736A01  
 30 B000020A14 72 D620735A01  
 31 B000020A18 73 C430401A02  
 32 D416322A01 74 D620939A01  
 33 B000026A12 75 B000026A07  
 34 C620408A01 76 B000021C01  
 35 C425262A01 77 C430401A02  
 36 B000020A58 78 C620949A03  
 37 D430283A01 79 C620820A01  
 38 C620261A01 80 C620824A01  
 39 C620463A01 81 C620842A01  
 40 C620464A01 82 C620884A01  
 41 C450663A01 83 C620841A01  
 42 D620484A01 84 C620860A07

85 B000023B01  
 86 D428123M01  
 87 D425202A01  
 88 D620226A09  
 89 D620241A01  
 90 D416302A01  
 91 D620361A01  
 92 D430283A01

Codice **A620000A09**  
 Modello **ML20**  
 Tipo Punto **90**  
 Lungh. min. **15 mm.**  
 Lungh. max. **32 mm.**

Code **A620000A09**  
 Model **ML20**  
 Staple type **90**  
 Min. length **15 mm.**  
 Max. length **32 mm.**

Code **A620000A09**  
 Modèle **ML20**  
 Agrafe type **90**  
 Longueur min. **15 mm.**  
 Longueur max. **32 mm.**

Código **A620000A09**  
 Modelo **ML20**  
 Grapa tipo **90**  
 Largueza min. **15 mm.**  
 Largueza max. **32 mm.**

Codigo **A620000A09**  
 Modelo **ML20**  
 Tipo de agrafe **90**  
 Largura min. **15 mm.**  
 Largura max. **32 mm.**

**DATI TECNICI**

Peso: **1350 gr.**  
 Dimensioni: **55-232-271 mm.**  
 Consumo aria: **0,64 NI/colpo (6 bar)**  
 Pressione min.: **4,0 bar**  
 Pressione max.: **7,0 bar**

**TECHNISCHE DATEN**

Gewicht: **1350 gr.**  
 Abmessungen: **55-232-271 mm.**  
 Luftverbrauch: **0,64 NI/pro Schlag (6 bar)**  
 Min.Betriebsdruck: **4,0 bar**  
 Max.Betriebsdruck: **7,0 bar**

**TECHNICAL FEATURES**

Weight: **1350 gr.**  
 Dimensions: **55-232-271 mm.**  
 Air consumption: **0,64 NI/shot (6 bar)**  
 Min.working pressure: **4,0 bar**  
 Max.working pressure: **7,0 bar**

**DONNEES TECHNIQUES**

Poids: **1350 gr.**  
 Dimensions: **55-232-271 mm.**  
 Consommation d'air: **0,64 NI/coup (6 bar)**  
 Pression de fonction min.: **4,0 bar**  
 Pression de fonction max.: **7,0 bar**

**DATOS TECNICOS**

Peso: **1350 gr.**  
 Dimensiones: **55-232-271 mm.**  
 Consumo de aire: **0,64 NI/disparo (6 bar)**  
 Presion min.: **4,0 bar**  
 Presion max.: **7,0 bar**

**CARACTERISTICAS TECNICAS**

Peso: **1350 gr.**  
 Dimensões: **55-232-271 mm.**  
 Consumo de ar: **0,64 NI/disparo (6 bar)**  
 Pressão min.: **4,0 bar**  
 Pressão max.: **7,0 bar**

**POTENZA ACUSTICA**

DIRETTIVA 89/392 CEE  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **82,5 (dB)**  
 LpA 60S 1M= **80,7 (dB)**

**SCHALLEISTUNG**

EWG RICHTLINIE 89/392  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **82,5 (dB)**  
 LpA 60S 1M= **80,7 (dB)**

**NOISE POWER**

EEC DIRECTIVE 89/392  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **82,5 (dB)**  
 LpA 60S 1M= **80,7 (dB)**

**PUISSANCE ACOUSTIQUE**

DIRECTIVE CEE 89/392  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **82,5 (dB)**  
 LpA 60S 1M= **80,7 (dB)**

**POTENCIA ACUSTICA**

NORMATIVA 89/392 CEE  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **82,5 (dB)**  
 LpA 60S 1M= **80,7 (dB)**

**POTENCIA ACUSTICA**

DIRETTIVA 89/392 CEE  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **82,5 (dB)**  
 LpA 60S 1M= **80,7 (dB)**

B620040A01 O-Ring Kit

**VIBRAZIONI PRODOTTE**

DIRETTIVA 89/392 CEE  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= inferiore a **2,5 (m/s<sup>2</sup>)**

**GERAETEBEZOGENER VIBRATIONSWERT**

EWG RICHTLINIE 89/392  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= unter **2,5 (m/s<sup>2</sup>)**

**TOOL RELATED VIBRATION VALUE**

EEC DIRECTIVE 89/392  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= below **2,5 (m/s<sup>2</sup>)**

**VALEUR DES VIBRATIONS PAR LA MACHINE**

DIRECTIVE CEE 89/392  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= inférieur à **2,5 (m/s<sup>2</sup>)**

**VIBRACION PRODUCIDA**

NORMATIVA 89/392 CEE  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= inferior a **2,5 (m/s<sup>2</sup>)**

**NIVEL DE VIBRAÇÃO DO PRODUTO**

DIRETTIVA 89/392 CEE  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= inferior a **2,5 (m/s<sup>2</sup>)**

620/0 A09/02 05/03