



RIF. COD.

1	B000028A10	43	C620503K01
2	C425100A01	44	C620500K01
3	C425103A02	45	B000028C04
4	D428123M01	46	B000022A01
5	B000020A40	47	B000028E03
6	B000020A39	48	B000021C01
7	C225160A01	49	D450441A01
8	B000020A04	50	C620424A01
9	C016200A01	51	B000028E14
10	D425202A01	52	B000022A02
11	B000020A36	53	B000023B02
12	B000020A33	54	C620701K01
13	B000020A31	55	B000028B32
14	C425220A01	56	B000028E06
15	B000025A12	57	B000022A01
16	C620226K03	58	C620768K01
17	C425242A01	59	B000028B22
18	B000020A39	60	C620769K01
19	D620241A01	61	C620737K01
20	B000020A24	62	C620951K01
21	C225244A01	63	B000023B01
22	B000020A17	64	C620697A01
23	D416302A01	65	B000021C03
24	B000020A01	66	C620699A01
25	B000020A03	67	C620698A03
26	D620361A01	68	C620684A01
27	C216340A01	69	C620600K03
28	B000020A14	70	B000021C03
29	D620345A01	71	C620551K01
30	B000020A14	72	C620524A01
31	B000020A18	73	D620670A01
32	D416322A01	74	C620540K05
33	B000026A12	75	C620740K01
34	C620408A01	76	B000028B03
35	C425262A01	77	C620737K01
36	B000020A58	78	C620720K01
37	D430283A01	79	B000028B31
38	C620261K01	80	B000022A02
39	C620463A01	81	C620938K05
40	C620464A01	82	B000022A02
41	C450663A01	83	B000028B31
42	D620484A01	84	B000028E06

Codice A620000K05

Modello ML20  
Tipo Punto 18  
Lungh. min. 20 mm.  
Lungh. max. 50 mm.

Kode A620000K05

Modell ML20  
Klammer Typ 18  
Min. Länge 20 mm.  
Max. Länge 50 mm.

Code A620000K05

Model ML20  
Staple type 18  
Min. length 20 mm.  
Max. length 50 mm.

Code A620000K05

Modèle ML20  
Agrafe type 18  
Longueur min. 20 mm.  
Longueur max. 50 mm.

Código A620000K05

Modelo ML20  
Grapa tipo 18  
Largueza min. 20 mm.  
Largueza max. 50 mm.

Codigo A620000K05

Modelo ML20  
Tipo de agrafe 18  
Largura min. 20 mm.  
Largura max. 50 mm.

DATI TECNICI

Peso: 1420 gr.  
Dimensioni: 55-234-285 mm.  
Consumo aria: 0,64 NI/colpo (6 bar)  
Pressione min.: 4,0 bar  
Pressione max.: 7,0 bar

TECHNISCHE DATEN

Gewicht: 1420 gr.  
Abmessungen: 55-234-285 mm.  
Luftverbrauch: 0,64 NI/pro Schlag (6 bar)  
Min.Betriebsdruck: 4,0 bar  
Max.Betriebsdruck: 7,0 bar

TECHNICAL FEATURES

Weight: 1420 gr.  
Dimensions: 55-234-285 mm.  
Air consumption: 0,64 NI/shot (6 bar)  
Min.working pressure: 4,0 bar  
Max.working pressure: 7,0 bar

DONNEES TECHNIQUES

Poids: 1420 gr.  
Dimensions: 55-234-285 mm.  
Consommation d'air: 0,64 NI/coup (6 bar)  
Pression de fonction min.: 4,0 bar  
Pression de fonction max.: 7,0 bar

DATOS TECNICOS

Peso: 1420 gr.  
Dimensiones: 55-234-285 mm.  
Consumo de aire: 0,64 NI/disparo (6 bar)  
Presion min.: 4,0 bar  
Presion max.: 7,0 bar

CARACTERISTICAS TECNICAS

Peso: 1420 gr.  
Dimensões: 55-234-285 mm.  
Consumo de ar: 0,64 NI/disparo (6 bar)  
Pressão min.: 4,0 bar  
Pressão max.: 7,0 bar

POTENZA ACUSTICA

DIRETTIVA 89/392 CEE  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= 82,5 (dB)  
LpA 60S 1M= 80,7 (dB)

SCHALLEISTUNG

EWG RICHTLINIE 89/392  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= 82,5 (dB)  
LpA 60S 1M= 80,7 (dB)

NOISE POWER

EEC DIRECTIVE 89/392  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= 82,5 (dB)  
LpA 60S 1M= 80,7 (dB)

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE 89/392  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= 82,5 (dB)  
LpA 60S 1M= 80,7 (dB)

POTENCIA ACUSTICA

NORMATIVA 89/392 CEE  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= 82,5 (dB)  
LpA 60S 1M= 80,7 (dB)

POTENCIA ACUSTICA

DIRETTIVA 89/392 CEE  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= 82,5 (dB)  
LpA 60S 1M= 80,7 (dB)

VIBRAZIONI PRODOTTE

DIRETTIVA 89/392 CEE  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= inferiore a 2,5 (m/s<sup>2</sup>)

GERAETEBEZOGENER VIBRATIONSWERT

EWG RICHTLINIE 89/392  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= unter 2,5 (m/s<sup>2</sup>)

TOOL RELATED VIBRATION VALUE

EEC DIRECTIVE 89/392  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= below 2,5 (m/s<sup>2</sup>)

VALEUR DES VIBRATIONS PAR LA MACHINE

DIRECTIVE CEE 89/392  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= inférieur à 2,5 (m/s<sup>2</sup>)

VIBRACION PRODUCIDA

NORMATIVA 89/392 CEE  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= inferior a 2,5 (m/s<sup>2</sup>)

NIVEL DE VIBRAÇÃO DO PRODUTO

DIRETTIVA 89/392 CEE  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= inferior a 2,5 (m/s<sup>2</sup>)

B620040A01 O-Ring Kit

620/0 K05/02 05/03