



**RIF. COD.**

1	B000028A12	40	C620463A01	79	B000028B31
2	C450101A01	41	C640464A01	80	B000022A02
3	C450103A01	42	C620465A01	81	C650938K01
4	B000028C04	43	D650484A01	82	B000022A02
5	C450180A01	44	C650503K01	83	B000028B31
6	D450123A01	45	C650500K01	84	B000022A01
7	C240160A01	46	B000028B20	85	B000028E06
8	B000020A06	47	B000022A01	86	C640742K03
9	C450181A01	48	B000028E03	87	B000023B01
10	B000020A45	49	B000021C01	88	C216661B01
11	D450202A01	50	D450441A01	89	C620949K01
12	B000020A42	51	C620424A01	90	C620820K03
13	B000020A40	52	B000028B14	91	C620824A01
14	D450204A01	53	B000022A02	92	C650842A01
15	B000020A47	54	B000023B02	93	C620884A01
16	B000023B04	55	C650701K01	94	C650860K01
17	B000020A54	56	B000028B32	95	D450123A01
18	C450220A01	57	B000028E06	96	D450202A01
19	C650225K01	58	B000022A01	97	D450204A01
20	B000020A42	59	C620768K01	98	D650226K01
21	D650241A01	60	B000028B22	99	D650241A01
22	B000020A41	61	C620769K01	100	D450243A01
23	B000020A50	62	C620737K01	101	D650304A01
24	D450243A01	63	C620951K01	102	D650361A01
25	C450244A01	64	B000023B01	103	D450283A01
26	B000020B02	65	C416761N01		
27	B000020B01	66	B000021C03		
28	B000020B10	67	C650699A01		
29	D650304A01	68	C650698A03		
30	B000020B10	69	C650684A01		
31	D650361A01	70	C650600A01		
32	B000020A19	71	B000021C03		
33	B000020A19	72	C650551K01		
34	B000026A12	73	C650524A01		
35	C620408A01	74	C650540K01		
36	C450262A01	75	B000028B03		
37	B000020A42	76	B000022A01		
38	D450283A01	77	C620737K01		
39	C650261A01	78	C640720K01		

Codice **A650000K03**  
Modello **ML50**  
Tipo Punto **TN2,2**  
Lungh. min. **30 mm.**  
Lungh. max. **65 mm.**

Kode **A650000K03**  
Modell **ML50**  
Klammer Typ **TN2,2**  
Min. Länge **30 mm.**  
Max. Länge **65 mm.**

Code **A650000K03**  
Model **ML50**  
Staple type **TN2,2**  
Min. length **30 mm.**  
Max. length **65 mm.**

Code **A650000K03**  
Modèle **ML50**  
Agrafe type **TN2,2**  
Longueur min. **30 mm.**  
Longueur max. **65 mm.**

Código **A650000K03**  
Modelo **ML50**  
Grapa tipo **TN2,2**  
Largueza min. **30 mm.**  
Largueza max. **65 mm.**

Codigo **A650000K03**  
Modelo **ML50**  
Tipo de agrafe **TN2,2**  
Largura min. **30 mm.**  
Largura max. **65 mm.**

**DATI TECNICI**

Peso: **2430 gr.**  
Dimensioni: **86-272-368 mm.**  
Consumo aria: **1,98 NI/colpo (6 bar)**  
Pressione min.: **4,0 bar**  
Pressione max.: **7,0 bar**

**TECHNISCHE DATEN**

Gewicht: **2430 gr.**  
Abmessungen: **86-272-368 mm.**  
Luftverbrauch: **1,98 NI/pro Schlag (6 bar)**  
Min.Betriebsdruck: **4,0 bar**  
Max.Betriebsdruck: **7,0 bar**

**TECHNICAL FEATURES**

Weight: **2430 gr.**  
Dimensions: **86-272-368 mm.**  
Air consumption: **1,98 NI/shot (6 bar)**  
Min.working pressure: **4,0 bar**  
Max.working pressure: **7,0 bar**

**DONNEES TECHNIQUES**

Poids: **2430 gr.**  
Dimensions: **86-272-368 mm.**  
Consommation d'air: **1,98 NI/coup (6 bar)**  
Pression de fonction min.: **4,0 bar**  
Pression de fonction max.: **7,0 bar**

**DATOS TECNICOS**

Peso: **2430 gr.**  
Dimensiones: **86-272-368 mm.**  
Consumo de aire: **1,98 NI/disparo (6 bar)**  
Presion min.: **4,0 bar**  
Presion max.: **7,0 bar**

**CARACTERISTICAS TECNICAS**

Peso: **2430 gr.**  
Dimensões: **86-272-368 mm.**  
Consumo de ar: **1,98 NI/disparo (6 bar)**  
Pressão min.: **4,0 bar**  
Pressão max.: **7,0 bar**

**POTENZA ACUSTICA**

DIRETTIVA 89/392 CEE  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,4 (dB)**  
LpA 60S 1M= **88,7 (dB)**

**SCHALLEISTUNG**

EWG RICHTLINIE 89/392  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,4 (dB)**  
LpA 60S 1M= **88,7 (dB)**

**NOISE POWER**

EEC DIRECTIVE 89/392  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,4 (dB)**  
LpA 60S 1M= **88,7 (dB)**

**PUISSANCE ACOUSTIQUE**

DIRECTIVE CEE 89/392  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,4 (dB)**  
LpA 60S 1M= **88,7 (dB)**

**POTENCIA ACUSTICA**

NORMATIVA 89/392 CEE  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,4 (dB)**  
LpA 60S 1M= **88,7 (dB)**

**POTENCIA ACUSTICA**

DIRETTIVA 89/392 CEE  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,4 (dB)**  
LpA 60S 1M= **88,7 (dB)**

**VIBRAZIONI PRODOTTE**

DIRETTIVA 89/392 CEE  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,8 (m/s²)**

**GERAETEBEZOGENER**

**VIBRATIONSWERT**  
EWG RICHTLINIE 89/392  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,8 (m/s²)**

**TOOL RELATED VIBRATION**

**VALUE**  
EEC DIRECTIVE 89/392  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,8 (m/s²)**

**VALEUR DES VIBRATIONS**

**PAR LA MACHINE**  
DIRECTIVE CEE 89/392  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,8 (m/s²)**

**VIBRACION PRODUCIDA**

NORMATIVA 89/392 CEE  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,8 (m/s²)**

**NIVEL DE VIBRACAO**

**DO PRODUTO**  
DIRETTIVA 89/392 CEE  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **2,8 (m/s²)**

B650040A01 O-Ring Kit

650/0 K03/01 02/04