



RIF. COD.

1	B000028A12	40	C451806U01	79	B000028E04
2	C450101A01	41	C451807U01	80	B000022D03
3	B000028C04	42	B000028B26	81	C451731U01
4	C450180A01	43	B000020A42	82	C451740U01
5	D450123A01	44	D450283A01	83	C451741U01
6	C240160A01	45	B000023A02	84	C451752U01
7	B000020A06	46	B000028D11	85	C451753U01
8	C450181A01	47	B000027B01	86	C451756U01
9	B000020A45	48	B000023B01	87	C451757U01
10	D450202A01	49	C450403A01	88	C451722U01
11	B000020A42	50	C450405A01	89	C451750U01
12	B000020A40	51	D450441A01	90	C451752U01
13	D450204A01	52	C430401A02	91	B000028B12
14	B000020A47	53	C430425A02	92	B000022C01
15	B000023B04	54	B000020B06	93	B000023B03
16	C451220A01	55	D451846U01	94	C451700U01
17	B000020A54	56	B000020B07	95	C451702U01
18	C451225U01	57	C451850U01	96	B000028B19
19	D451241A01	58	C451842U01	97	C451807U01
20	B000020A42	59	C451885U01	98	C451824U01
21	B000020A41	60	B000021A02	99	D450123A01
22	B000020A50	61	C451807U01	100	D450202A01
23	D450243A01	62	C451524U01	101	D450204A01
24	C451244U01	63	C451807U01	102	D451226U01
25	C451261A01	64	C451872U01	103	D451241A01
26	B000023B03	65	C451851U01	104	D450243A01
27	C565180A01	66	C451852U01	105	D451546U01
28	C451681U01	67	C451551U01	106	D451874U01
29	B000026A05	68	C451765U01	107	D450283A01
30	B000020A16	69	C451766U01	108	D450441A01
31	B000020A68	70	B000026B02	109	D451846U01
32	D451546U01	71	B000020B02	110	D450304A01
33	B000022C02	72	B000020B01	111	D450361A01
34	B000028B25	73	B000020A02		
35	C451661U01	74	D450304A01		
36	D451640U01	75	B000020A02		
37	C451826U01	76	D450361A01		
38	D451874U01	77	B000020A19		
39	B000026B03	78	B000020A19		

Codice **A651000U01**  
Modello **ML51**  
Tipo Punto **CN**  
Lungh. min. **25 mm.**  
Lungh. max. **60 mm.**

Kode **A651000U01**  
Modell **ML51**  
Klammer Typ **CN**  
Min. Länge **25 mm.**  
Max. Länge **60 mm.**

Code **A651000U01**  
Model **ML51**  
Staple type **CN**  
Min. length **25 mm.**  
Max. length **60 mm.**

Code **A651000U01**  
Modèle **ML51**  
Agrafe type **CN**  
Longueur min. **25 mm.**  
Longueur max. **60 mm.**

Código **A651000U01**  
Modelo **ML51**  
Grapa tipo **CN**  
Largueza min. **25 mm.**  
Largueza max. **60 mm.**

Codigo **A651000U01**  
Modelo **ML51**  
Tipo de agrafe **CN**  
Largura min. **25 mm.**  
Largura max. **60 mm.**

DATI TECNICI

Peso: **2670 gr.**  
Dimensioni: **126-274-282 mm.**  
Consumo aria: **2,00 NI/colpo (6 bar)**  
Pressione min.: **4,0 bar**  
Pressione max.: **7,0 bar**

TECHNISCHE DATEN

Gewicht: **2670 gr.**  
Abmessungen: **126-274-282 mm.**  
Luftverbrauch: **2,00 NI/pro Schlag (6 bar)**  
Min. Betriebsdruck: **4,0 bar**  
Max. Betriebsdruck: **7,0 bar**

TECHNICAL FEATURES

Weight: **2670 gr.**  
Dimensions: **126-274-282 mm.**  
Air consumption: **2,00 NI/shot (6 bar)**  
Min. working pressure: **4,0 bar**  
Max. working pressure: **7,0 bar**

DONNEES TECHNIQUES

Poids: **2670 gr.**  
Dimensions: **126-274-282 mm.**  
Consommation d'air: **2,00 NI/coup (6 bar)**  
Pression de fonction min.: **4,0 bar**  
Pression de fonction max.: **7,0 bar**

DATOS TECNICOS

Peso: **2670 gr.**  
Dimensiones: **126-274-282 mm.**  
Consumo de aire: **2,00 NI/disparo (6 bar)**  
Presion min.: **4,0 bar**  
Presion max.: **7,0 bar**

CARACTERISTICAS TECNICAS

Peso: **2670 gr.**  
Dimensões: **126-274-282 mm.**  
Consumo de ar: **2,00 NI/disparo (6 bar)**  
Pressão min.: **4,0 bar**  
Pressão max.: **7,0 bar**

POTENZA ACUSTICA

DIRETTIVA 89/392 CEE  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,7 (dB)**  
LpA 60S 1M= **88,9 (dB)**

SCHALLEISTUNG

EWG RICHTLINIE 89/392  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,7 (dB)**  
LpA 60S 1M= **88,9 (dB)**

NOISE POWER

EEC DIRECTIVE 89/392  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,7 (dB)**  
LpA 60S 1M= **88,9 (dB)**

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE 89/392  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,7 (dB)**  
LpA 60S 1M= **88,9 (dB)**

POTENCIA ACUSTICA

NORMATIVA 89/392 CEE  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,7 (dB)**  
LpA 60S 1M= **88,9 (dB)**

POTENCIA ACUSTICA

DIRETTIVA 89/392 CEE  
prEN 12549 (1999)  
UNI EN ISO 3744 (1997)  
LwA= **89,7 (dB)**  
LpA 60S 1M= **88,9 (dB)**

VIBRAZIONI PRODOTTE

DIRETTIVA 89/392 CEE  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **3 (m/s²)**

GERAETEBEZOGENER VIBRATIONSWERT

EWG RICHTLINIE 89/392  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **3 (m/s²)**

TOOL RELATED VIBRATION VALUE

EEC DIRECTIVE 89/392  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **3 (m/s²)**

VALEUR DES VIBRATIONS PAR LA MACHINE

DIRECTIVE CEE 89/392  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **3 (m/s²)**

VIBRACION PRODUCIDA

NORMATIVA 89/392 CEE  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **3 (m/s²)**

NIVEL DE VIBRACAO DO PRODUTO

DIRETTIVA 89/392 CEE  
ISO/FDIS 8662-11 (1999)  
ah.w.3s= **3 (m/s²)**

B651040U01 O-Ring Kit

651/0 U01/01 02/11