



RIF.	COD.			<u>DATI TECNICI</u>	<u>POTENZA ACUSTICA</u>	<u>VIBRAZIONI PRODOTTE</u>
1	B000028A04	43	B000028B01	Codice A710000B09	Peso: 850 gr.	DIRETTIVA 89/392 CEE
2	C416100A01	44	C416681B01	Modello M10 SIC	Dimensioni: 44-161-222 mm.	DIRETTIVA 89/392 CEE
3	C416103A02	45	C216661B01	Tipo Punto 14	Consumo aria: 0,24 NI/colpo (6 bar)	ISO/FDIS 8662-11 (1999)
4	D416123A01	46	C610600B01	Lungh. min. 6 mm.	Pressione min.: 4,0 bar	ah.w.3s= inferiore a 2,5 (m/s ²)
5	B000020A36	47	B000021C01	Lungh. max. 16 mm.	Pressione max.: 7,0 bar	
6	C216160A01	48	B000028B04			
7	B000020A19	49	C610542B11	Kode A710000B09	<u>TECHNISCHE DATEN</u>	<u>SCHALLEISTUNG</u>
8	C016200A01	50	C416500A01	Modell M10 SIC	Gewicht: 850 gr.	EWG RICHTLINIE 89/392
9	D416202A02	51	C416722A03	Klammer Typ 14	Abmessungen: 44-161-222 mm.	prEN 12549 (1999)
10	B000020A35	52	B000021C01	Min. Länge 6 mm.	Luftverbrauch: 0,24 NI/pro Schlag (6 bar)	UNI EN ISO 3744 (1997)
11	B000020A31	53	C216424A01	Max. Länge 16 mm.	Min.Betriebsdruck: 4,0 bar	LwA= 80,3 (dB)
12	C416220A01	54	B000028A04		Max.Betriebsdruck: 7,0 bar	LpA 60S 1M= 78,9 (dB)
13	B000025A06	55	C416990A01			
14	C610225A11	56	B000021C01	Code A710000B09	<u>TECHNICAL FEATURES</u>	<u>NOISE POWER</u>
15	B000020A29	57	B000028A06	Model M10 SIC	Weight: 850 gr.	EEC DIRECTIVE 89/392
16	D416241A02	58	B000023B02	Staple type 14	Dimensions: 44-161-222 mm.	prEN 12549 (1999)
17	B000020A35	59	C416763A01	Min. length 6 mm.	Air consumption: 0,24 NI/shot (6 bar)	UNI EN ISO 3744 (1997)
18	B000020A22	60	B000026A05	Max. length 16 mm.	Min.working pressure: 4,0 bar	LwA= 80,3 (dB)
19	C016244A01	61	D416984A65		Max.working pressure: 7,0 bar	LpA 60S 1M= 78,9 (dB)
20	B000020A17	62	C416860A04			
21	D416302A01	63	C216842A01	Code A710000B09	<u>DONNEES TECHNIQUES</u>	<u>PUISSANCE ACOUSTIQUE</u>
22	B000020A01	64	C225884A01	Modèle M10 SIC	Poids: 850 gr.	DIRECTIVE CEE 89/392
23	B000020A03	65	D416123A01	Agrafe type 14	Dimensions: 44-161-222 mm.	prEN 12549 (1999)
24	D416361A01	66	D416202A02	Longueur min. 6 mm.	Consommation d'air: 0,24 NI/coup (6 bar)	UNI EN ISO 3744 (1997)
25	C216340A01	67	D610226A11	Longueur max. 16 mm.	Pression de fonction min.: 4,0 bar	LwA= 80,3 (dB)
26	B000020A14	68	D416241A02		Pression de fonction max.: 7,0 bar	LpA 60S 1M= 78,9 (dB)
27	D416345A01	69	D416302A01			
28	B000020A14	70	D416361A01	Código A710000B09	<u>DATOS TECNICOS</u>	<u>POTENCIA ACUSTICA</u>
29	B000020A18	71	D216283A01	Modelo M10 SIC	Peso: 850 gr.	NORMATIVA 89/392 CEE
30	D416322A01	72	D416984A65	Grapa tipo 14	Dimensiones: 44-161-222 mm.	prEN 12549 (1999)
31	C416431B01			Largueza min. 6 mm.	Consumo de aire: 0,24 NI/disparo (6 bar)	UNI EN ISO 3744 (1997)
32	C425262A01			Largueza max. 16 mm.	Presion min.: 4,0 bar	LwA= 80,3 (dB)
33	B000027B03				Presion max.: 7,0 bar	LpA 60S 1M= 78,9 (dB)
34	B000026A08					
35	B000020A36			Codigo A710000B09	<u>CARACTERISTICAS TECNICAS</u>	<u>POTENCIA ACUSTICA</u>
36	D216283A01			Modelo M10 SIC	Peso: 850 gr.	DIRETTIVA 89/392 CEE
37	C416764A01			Tipo de agrafe 14	Dimensões: 44-161-222 mm.	prEN 12549 (1999)
38	C016761A01			Largura min. 6 mm.	Consumo de ar: 0,24 NI/disparo (6 bar)	UNI EN ISO 3744 (1997)
39	C416760A01			Largura max. 16 mm.	Pressão min.: 4,0 bar	LwA= 80,3 (dB)
40	C416261A02				Pressão max.: 7,0 bar	LpA 60S 1M= 78,9 (dB)
41	C016483B01					
42	B000028B06					

B610040A01 O-Ring Kit

710/0 B09/01 07/11