



<u>RIF.</u>	<u>COD.</u>			<u>DATI TECNICI</u>	<u>POTENZA ACUSTICA</u>	<u>VIBRAZIONI PRODOTTE</u>
1	B000028A04	43	B000020A03	Codice A710003G03	Peso: 1030 gr.	DIRETTIVA 89/392 CEE
2	C416100A01	44	C416262A01	Modello M10 AUTO CL	Dimensioni: 48-155-337 mm.	ISO/FDIS 8662-11 (1999)
3	D416123A03	45	C216420A01	Tipo Punto 64	Consumo aria: 0,25 NI/colpo (6 bar)	ah.w.3s= inferiore a 2,5 (m/s <sup>2</sup> )
4	B000020A36	46	B000020A36	Lungh. min. 6 mm.	Pressione min.: 4,0 bar	
5	C216160A01	47	D216283A01	Lungh. max. 16 mm.	Pressione max.: 7,0 bar	
6	B000020A19	48	B000023B02			
7	C016200A01	49	B000028B05	Kode A710003G03	<u>TECHNISCHE DATEN</u>	<u>SCHALLEISTUNG</u>
8	D416202A02	50	B000022A01	Modell M10 AUTO CL	Gewicht: 1030 gr.	EWG RICHTLINIE 89/392
9	B000020A35	51	C416540A63	Klammer Typ 64	Abmessungen: 48-155-337 mm.	prEN 12549 (1999)
10	B000020A31	52	C416500A02	Min. Länge 6 mm.	Luftverbrauch: 0,25 NI/pro Schlag (6 bar)	UNI EN ISO 3744 (1997)
11	C416220A01	53	C416722G13	Max. Länge 16 mm.	Min.Betriebsdruck: 4,0 bar	LwA= 102,1 (dB)
12	B000025A06	54	B000023B01		Max.Betriebsdruck: 7,0 bar	LpA 60S 1M= 99,8 (dB)
13	C416225A63	55	D416427A01			
14	B000020A29	56	B000028A06	Code A710003G03	<u>TECHNICAL FEATURES</u>	<u>NOISE POWER</u>
15	D416241A02	57	B000028A04	Model M10 AUTO CL	Weight: 1030 gr.	EEC DIRECTIVE 89/392
16	B000020A35	58	C416990A01	Staple type 64	Dimensions: 48-155-337 mm.	prEN 12549 (1999)
17	B000020A22	59	C016761A01	Min. length 6 mm.	Air consumption: 0,25 NI/shot (6 bar)	UNI EN ISO 3744 (1997)
18	C416244A02	60	B000021C01	Max. length 16 mm.	Min.working pressure: 4,0 bar	LwA= 102,1 (dB)
19	D416350A02	61	C416760G02		Max.working pressure: 7,0 bar	LpA 60S 1M= 99,8 (dB)
20	B000020A14	62	C416763A01			
21	D416261A02	63	B000026A05	Code A710003G03	<u>DONNEES TECHNIQUES</u>	<u>PUISSANCE ACOUSTIQUE</u>
22	B000021C01	64	D416984G73	Modèle M10 AUTO CL	Poids: 1030 gr.	DIRECTIVE CEE 89/392
23	B000020A15	65	C416860A02	Agrafe type 64	Dimensions: 48-155-337 mm.	prEN 12549 (1999)
24	B000020A62	66	C416842G01	Longueur min. 6 mm.	Consommation d'air: 0,25 NI/coup (6 bar)	UNI EN ISO 3744 (1997)
25	D416364A01	67	C225884A01	Longueur max. 16 mm.	Pression de fonction min.: 4,0 bar	LwA= 102,1 (dB)
26	C416352A01	68	D416123A03		Pression de fonction max.: 7,0 bar	LpA 60S 1M= 99,8 (dB)
27	C416351A01	69	D416202A02			
28	B000020A16	70	D416226A63	Código A710003G03	<u>DATOS TECNICOS</u>	<u>POTENCIA ACUSTICA</u>
29	B000020A16	71	D416241A02	Modelo M10 AUTO CL	Peso: 1030 gr.	NORMATIVA 89/392 CEE
30	D416304A01	72	D416350A02	Grapa tipo 64	Dimensiones: 48-155-337 mm.	prEN 12549 (1999)
31	B000020A62	73	D416364A01	Largueza min. 6 mm.	Consumo de aire: 0,25 NI/disparo (6 bar)	UNI EN ISO 3744 (1997)
32	C416306A01	74	D416304A01	Largueza max. 16 mm.	Presion min.: 4,0 bar	LwA= 102,1 (dB)
33	B000020A15	75	D416325A01		Presion max.: 7,0 bar	LpA 60S 1M= 99,8 (dB)
34	D416325A01	76	D416345A02			
35	B000020A19	77	D416322A02	Codigo A710003G03	<u>CARACTERISTICAS TECNICAS</u>	<u>POTENCIA ACUSTICA</u>
36	C216340A01	78	D216283A01	Modelo M10 AUTO CL	Peso: 1030 gr.	DIRETTIVA 89/392 CEE
37	B000020A14	79	D416984G73	Tipo de agrafe 64	Dimensões: 48-155-337 mm.	prEN 12549 (1999)
38	B000020A14			Largura min. 6 mm.	Consumo de ar: 0,25 NI/disparo (6 bar)	UNI EN ISO 3744 (1997)
39	D416345A02			Largura max. 16 mm.	Pressão min.: 4,0 bar	LwA= 102,1 (dB)
40	B000020A14				Pressão max.: 7,0 bar	LpA 60S 1M= 99,8 (dB)
41	B000020A63					
42	D416322A02					
						B610040A03 O-Ring Kit
						710/3 G03/01 07/11