



RIF. COD.

1	B000028A11	43	C630500K03	85	C630742K01	Codice A730000K03
2	C430101A01	44	B000028C04	86	B000023B01	Modello M30
3	C430103A01	45	B000022A01	87	C216661B01	Tipo Punto FNT
4	B000028C04	46	B000028E03	88	C620949K01	Lungh. min. 15 mm.
5	C450180A01	47	B000021C01	89	C620820K01	Lungh. max. 40 mm.
6	D430123A01	48	D450441A01	90	C620824A01	
7	C225160A01	49	C620424A01	91	C650842A01	Kode A730000K03
8	B000020A04	50	B000028E14	92	C620884A01	Modell M30
9	C430181A01	51	B000022A02	93	C630860K03	Klammer Typ FNT
10	B000020A58	52	B000023B02	94	D430123A01	Min. Länge 15 mm.
11	D430202A02	53	C630701K01	95	D430202A02	Max. Länge 40 mm.
12	B000020A59	54	B000028B32	96	D430204A02	
13	B000020A24	55	B000028E06	97	D630226K03	
14	D430204A02	56	B000022A01	98	D630241A01	Code A730000K03
15	B000020A71	57	C620768K01	99	D430304A01	Model M30
16	B000023B05	58	B000028B22	100	D630361A01	Staple type FNT
17	B000020A61	59	C620769K01	101	D430283A01	Min. length 15 mm.
18	C630220K01	60	C620737K01			Max. length 40 mm.
19	C630225K03	61	C620951K01			
20	B000020A41	62	B000023B01			
21	D630241A01	63	C620697A01			Code A730000K03
22	B000020A36	64	B000021C03			Modèle M30
23	C430244A01	65	C620699A01			Agrafe type FNT
24	B000020B02	66	C620698A03			Longueur min. 15 mm.
25	B000020B01	67	C620684A01			Longueur max. 40 mm.
26	B000020A02	68	C630600K01			
27	D430304A01	69	B000021C03			
28	B000020A02	70	C630551K01			Código A730000K03
29	D630361A01	71	C620524A01			Modelo M30
30	B000020A19	72	D620670A01			Grapa tipo FNT
31	B000020A19	73	C630540K05			Largueza min. 15 mm.
32	B000026A12	74	B000028B03			Largueza max. 40 mm.
33	C620408A01	75	B000022A01			
34	C425262A01	76	C620737K01			
35	B000020A58	77	C630720K01			Codigo A730000K03
36	D430283A01	78	B000028B31			Modelo M30
37	C630261A01	79	B000022A02			Tipo de agrafe FNT
38	C620463A01	80	C630938K05			Largura min. 15 mm.
39	C620464A01	81	B000022A02			Largura max. 40 mm.
40	C450663A01	82	B000028B31			
41	D630484A01	83	B000022A01			
42	C630503K03	84	B000028E06			

DATI TECNICI

Peso: **1650 gr.**
 Dimensioni: **65-227-355 mm.**
 Consumo aria: **0,74 NI/colpo (6 bar)**
 Pressione min.: **4,0 bar**
 Pressione max.: **7,0 bar**

TECHNISCHE DATEN

Gewicht: **1650 gr.**
 Abmessungen: **65-227-355 mm.**
 Luftverbrauch: **0,74 NI/pro Schlag (6 bar)**
 Min.Betriebsdruck: **4,0 bar**
 Max.Betriebsdruck: **7,0 bar**

TECHNICAL FEATURES

Weight: **1650 gr.**
 Dimensions: **65-227-355 mm.**
 Air consumption: **0,74 NI/shot (6 bar)**
 Min.working pressure: **4,0 bar**
 Max.working pressure: **7,0 bar**

DONNEES TECHNIQUES

Poids: **1650 gr.**
 Dimensions: **65-227-355 mm.**
 Consommation d'air: **0,74 NI/coup (6 bar)**
 Pression de fonction min.: **4,0 bar**
 Pression de fonction max.: **7,0 bar**

DATOS TECNICOS

Peso: **1650 gr.**
 Dimensiones: **65-227-355 mm.**
 Consumo de aire: **0,74 NI/disparo (6 bar)**
 Presion min.: **4,0 bar**
 Presion max.: **7,0 bar**

CARACTERISTICAS TECNICAS

Peso: **1650 gr.**
 Dimensões: **65-227-355 mm.**
 Consumo de ar: **0,74 NI/disparo (6 bar)**
 Pressão min.: **4,0 bar**
 Pressão max.: **7,0 bar**

POTENZA ACUSTICA

DIRETTIVA 89/392 CEE
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **84,6 (dB)**
 LpA 60S 1M= **83,4 (dB)**

SCHALLEISTUNG

EWG RICHTLINIE 89/392
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **84,6 (dB)**
 LpA 60S 1M= **83,4 (dB)**

NOISE POWER

EEC DIRECTIVE 89/392
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **84,6 (dB)**
 LpA 60S 1M= **83,4 (dB)**

PUISSANCE ACOUSTIQUE VALEUR DES VIBRATIONS

DIRECTIVE CEE 89/392
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **84,6 (dB)**
 LpA 60S 1M= **83,4 (dB)**

POTENCIA ACUSTICA

NORMATIVA 89/392 CEE
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **84,6 (dB)**
 LpA 60S 1M= **83,4 (dB)**

POTENCIA ACUSTICA

DIRETTIVA 89/392 CEE
 prEN 12549 (1999)
 UNI EN ISO 3744 (1997)
 LwA= **84,6 (dB)**
 LpA 60S 1M= **83,4 (dB)**

VIBRAZIONI PRODOTTE

DIRETTIVA 89/392 CEE
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **inferiore a 2,5 (m/s²)**

GERAETEBEZOGENER

VIBRATIONSWERT
 EWG RICHTLINIE 89/392
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **unter 2,5 (m/s²)**

TOOL RELATED VIBRATION

VALUE
 EEC DIRECTIVE 89/392
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **below 2,5 (m/s²)**

VALEUR DES VIBRATIONS

PAR LA MACHINE
 DIRECTIVE CEE 89/392
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **inférieur à 2,5 (m/s²)**

VIBRACION PRODUCIDA

NORMATIVA 89/392 CEE
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **inferior a 2,5 (m/s²)**

NIVEL DE VIBRAÇÃO

DO PRODUTO
 DIRETTIVA 89/392 CEE
 ISO/FDIS 8662-11 (1999)
 ah.w.3s= **inferior a 2,5 (m/s²)**

B630040A01 O-Ring Kit

730/0 K03/01 07/11