



RIF. COD.

1	B000028A24	43	C750261A02	85	D750243A01
2	C750104A01	44	C750500A02	86	D750226K05
3	B000020A04	45	D750441A01	87	D750241A01
4	C750100A01	46	B000026A11	88	D750304A01
5	C565103A01	47	B000028B14	89	D750361A01
6	B000028C07	48	C450180A01	90	D450283A01
7	C750180A01	49	C750701K01		
8	D750123A01	50	C450703K01		
9	B000020A37	51	C750720K01		
10	C750181A01	52	B000021C01		
11	C750200A01	53	D750484A01		
12	B000020A38	54	C750689A01		
13	B000020A44	55	B000022A01		
14	D790202U01	56	B000028E03		
15	B000020A42	57	B000026A11		
16	C750162A01	58	B000028B12		
17	C750246A03	59	B000022C01		
18	B000020A44	60	C450724K01		
19	D750243A01	61	B000028B13		
20	B000020A76	62	B000022C01		
21	C790222K03	63	B000028B04		
22	B000021F01	64	C750681K05		
23	B000020A38	65	C230661A01		
24	C750220K01	66	C750600K01		
25	C450225K04	67	B000028B20		
26	D750241A01	68	C750507A01		
27	B000020A43	69	B000028C04		
28	C450244A01	70	C750540K07		
29	B000020B02	71	D450984K02		
30	B000020B01	72	B000023C01		
31	D750304A01	73	C275801K01		
32	B000020A02	74	D450871K01		
33	B000020B11	75	C275843K01		
34	B000020A02	76	B000028A13		
35	D750361A01	77	C450944K01		
36	B000020A19	78	C450942K01		
37	B000020A19	79	C450943K01		
38	B000026A12	80	C450746K01		
39	D750411A02	81	C450747K01		
40	C450262A01	82	B000028B01		
41	B000020A42	83	D750123A01		
42	D450282A01	84	D790202U01		

Codice **A750000K07**
Modello **M50**
Tipo Punto **PINS**
Lungh. min. **25 mm.**
Lungh. max. **50 mm.**

Kode **A750000K07**
Modell **M50**
Klammer Typ **PINS**
Min. Länge **25 mm.**
Max. Länge **50 mm.**

Code **A750000K07**
Model **M50**
Staple type **PINS**
Min. length **25 mm.**
Max. length **50 mm.**

Code **A750000K07**
Modèle **M50**
Agrafe type **PINS**
Longueur min. **25 mm.**
Longueur max. **50 mm.**

Código **A750000K07**
Modelo **M50**
Grapa tipo **PINS**
Largueza min. **25 mm.**
Largueza max. **30 mm.**

Codigo **A750000K07**
Modelo **M50**
Tipo de agrafe **PINS**
Largura min. **25 mm.**
Largura max. **50 mm.**

DATI TECNICI

Peso: **2750 gr.**
Dimensioni: **86-282-367 mm.**
Consumo aria: **2,12 NI/colpo (6 bar)**
Pressione min.: **5,0 bar**
Pressione max.: **8,0 bar**

TECHNISCHE DATEN

Gewicht: **2750 gr.**
Abmessungen: **86-282-367 mm.**
Luftverbrauch: **2,12 NI/pro Schlag (6 bar)**
Min.Betriebsdruck: **5,0 bar**
Max.Betriebsdruck: **8,0 bar**

TECHNICAL FEATURES

Weight: **2750 gr.**
Dimensions: **86-282-367 mm.**
Air consumption: **2,12 NI/shot (6 bar)**
Min.working pressure: **5,0 bar**
Max.working pressure: **8,0 bar**

DONNEES TECHNIQUES

Poids: **2750 gr.**
Dimensions: **86-282-367 mm.**
Consommation d'air: **2,12 NI/coup (6 bar)**
Pression de fonction min.: **5,0 bar**
Pression de fonction max.: **8,0 bar**

DATOS TECNICOS

Peso: **2750 gr.**
Dimensiones: **86-282-367 mm.**
Consumo de aire: **2,12 NI/disparo (6 bar)**
Presion min.: **5,0 bar**
Presion max.: **8,0 bar**

CARACTERISTICAS TECNICAS

Peso: **2750 gr.**
Dimensões: **86-282-367 mm.**
Consumo de ar: **2,12 NI/disparo (6 bar)**
Pressão min.: **5,0 bar**
Pressão max.: **8,0 bar**

POTENZA ACUSTICA

DIRETTIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **89,5 (dB)**
LpA 60S 1M= **82,1 (dB)**

SCHALLEISTUNG

EWG RICHTLINIE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **89,5 (dB)**
LpA 60S 1M= **82,1 (dB)**

NOISE POWER

EEC DIRECTIVE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **89,5 (dB)**
LpA 60S 1M= **82,1 (dB)**

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **89,5 (dB)**
LpA 60S 1M= **82,1 (dB)**

POTENCIA ACUSTICA

NORMATIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **89,5 (dB)**
LpA 60S 1M= **82,1 (dB)**

POTENCIA ACUSTICA

DIRETTIVA CEE
ISO-11148-13-2017
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= **89,5 (dB)**
LpA 60S 1M= **82,1 (dB)**

B650040K01 O-Ring Kit

VIBRAZIONI PRODOTTE

DIRETTIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **2,8 (m/s²)**

GERAETEBEZOGENER

VIBRATIONSWERT
EWG RICHTLINIE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **2,8 (m/s²)**

TOOL RELATED VIBRATION

VALUE
EEC DIRECTIVE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **2,8 (m/s²)**

VALEUR DES VIBRATIONS

PAR LA MACHINE
DIRECTIVE CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **2,8 (m/s²)**

VIBRACION PRODUCIDA

NORMATIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **2,8 (m/s²)**

NIVEL DE VIBRAÇÃO

DO PRODUTO
DIRETTIVA CEE
ISO-11148-13-2017
ISO/FDIS 8662-11 (1999)
ah.w.3s= **2,8 (m/s²)**

750/0 K07/01 17/05