

M45 – CN 60 COIL NAILER



SPECIFICATIONS		
M45 - CN/60	Weight	2,43 kg. / 5,3 lbs
	Dimensions W x H x L	134-280-274 mm / 5 5/16" - 11 1/16" – 10 13/16"
	Pressure min - max	5 - 8 bar
	Air Consumption at 6 bar	2,00 NI/shot
	Operation (trigger switch system)	Single shot & Contact trip service
	Noise value - EEC Directive 89/392 PrEN 12549(1999) UNI EN ISO 3744 (1997)	LwA= 89,2 dB – LpA 60s 1m = 81,9 dB
	Vibration value (m/s ²) EEC Directive 89/392 ISO/FDIS 8662-11 (1999)	ah.w.3s = 2,8 m/s ²
	Drive Depth regulator for fasteners	STANDARD ON TOOL

Fasteners		
CN/60	Smooth, screw and ring shank, flat wound wire collated nails - 15-16°	
	Length min – max	25 – 60 mm. (1" – 2 3/8")
	Wire Diameter	From 2,1 to 2,5 mm. (0.080"-0.097")
	Head Diameter	From 5,0 to 6,2 mm. (0,19" – 0.24")

Magazine		
	Capacity	360 nails

Features & Benefits	Applications
<ul style="list-style-type: none"> • Perfect balance and light weight • Improved professional performance thanks to the new powerful body • Ruggedly built for industry applications and construction site • High impact composite material magazine • Exhausted air flow at 360° • Excellent job visibility • Anti-double shot mechanism 	<ul style="list-style-type: none"> • Wood carpentry • Pre-fabricated housing • Production of medium and heavy duty wood packaging • Manufacturing of cases, crates and pallets