

M50 - PINS /50



SPECIFICATIONS

M50 PINS	Weight		2,54 kg. / 5,6 lbs
	Dimensions H x L	W x	86-267-368 mm / 3 3/8"- 10 1/2"- 14 1/2"
	Pressure - max	min	4 - 7 bar
	Air Consumption bar	at 6	2,8 NI/shot
	Operation		Contact trip service
	Noise value - EEC Directive 89/392 PrEN 12549(1999) UNI EN ISO 3744 (1997)		LwA= 89,4 dB - LpA 60s 1m = 88,7 dB
	Vibration value (m/s ²) EEC Directive 89/392 ISO/FDIS 8662-11(1999)		ah.w.3s = 2,8 m/s ²

Fasteners

/50	ALUMINIUM PINS		
	Length	min - max	25 - 50 mm. (1" - 2")
	Wire diam.		2,4 - 2,8 mm. (0,09" - 0,11")

Magazine

	Capacity		90 pins
--	-----------------	--	---------

Features & Benefits

- Perfect balance and light weight
- High power for hard wood applications
- Standard with safety on the nose
- Exhausted air flow at 360°
- Top loading magazine

Applications

- Frames, Furniture assembly
- Mobile Homes- fencing
- Insulation, sheathing